

TENDER DOCUMENT

FOR

SUPPLY, INSTALLATION, TESTING, COMMISSIONING AND TRIAL RUN OF

DAIRY EQUIPMENTS

AT

TIRTOL DAIRY



THE ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD.

D-2, SAHID NAGAR BHUBANESWAR -751007

<u>January -2024</u> <u>Cost : Rs.5,000/- +18% GST</u>

THE ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD, D-2, SAHEED NAGAR, BHUBANESWAR, ORISSA.

TELEPHONES: (0674)-2546121, 2544576, 2540417, 546030, 2540273 FAX: 0674-2506974

Email: omfed@yahoo.com web site: www.omfed.com

TENDER FOR:

SUPPLY, INSTALLATION, TESTING, COMMISSIONG AND TRIAL RUN OF DAIRY EQUIPMENTS AT TIRTOL DAIRY OF OMFED.

LOCATION OF DAIRY SITE : TIRTOL DAIRY

TENDER REFERENCE : PROJ/229/Tirtol Dairy/23

DATE OF COMMENCEMENT TO DOWN

LOAD OF BIDDING DOCUMENT

: 05.01.2024

DATE OF PRE - BID MEETING : 12.01.2024 at 1500 hours

LAST DATE FOR DOWN LOAD OF

BIDDING DOCUMENT / ONLINE BIDDING

: 29.01.2024 UPTO 1400 hours

DATE AND TIME FOR RECEIPT

OF BIDDING DOCUMENTS

: 29.01.2024 at 1400 hours

DATE AND TIME OF OPENING OF

TECHNICAL BIDS

: 29.01.2024 at 1500 hours

PLACE OF OPENING OF BIDS : OFFICE OF THE ORISSA STATE

COOP.MILK PRODUCERS FED.LTD. D-2, SAHEEDNAGAR, BHUBANESWAR,

ODISHA.

ADDRESS FOR COMMUNICATION: THE ORISSA STATE CO- OP. MILK

PRODUCERS' FEDERATION. LTD.

D-2, SAHEEDNAGAR, BHUBANESWAR-

ODISHA, INDIA.751007

TABLE OF CONTENTS

SECTION	SUBJECT	PAGE	
I TENDER NOTICE		4	
II	INSTRUCTIONS TO BIDDERS	5	
III	GENERAL CONDITIONS OF CONTRACT	16	
IV	SPECIAL CONDITIONS OF CONTRACT (ERECTION& COMMISSIONING)	27	
IV (A)	SPECIAL CONDITIONS OF CONTRACT (MECHANICAL INSTALLATION)	41	
IV (B)	SPECIAL CONDITIONS OF CONTRACT (ELECTRICAL INSTALLATION)	45	
V	TECHNICAL SPECIFICATIONS	47	
VI	COMMERCIAL BID	66	
VII	BID FORM	67	
VIII	QUALIFICATION APPLICATION	70	
IX	FORM OF AGREEMENT	73	
X	ACCEPTABLE FORMS OF BANK GUARANTEE	76	
XI (1)	MANUFACTURERS' AUTHORISATION FORM	85	
XI (2)	MANUFACTURERS' AUTHORISATION FORM	87	
XII	TECHNICAL DEVIATION STATEMENT FORM	89	
XIII	POINTS BIDDERS SHOULD BEAR IN MIND	90	

SPECIFICATION CONTENTS

SI No	Name of equipment	Capacity	Quantity (nos)	Page No.
1	Online Milk Pasteuriser	5KLPH	1	47
2	Online Milk Homogeniser	5KLPH	1	50
3	Online Cream Separator	5KLPH	1	52
4	Milk Can Washer	600 Cans/hr.	1	53
5	Milk Silo	10 KL	1	56
6	Two Stage PHE	1KLPH	1	56
7	Multi Purpose Vat	1 KL	1	56
8	Khoa / Rabidi Pan	240 Ltr	1	59
9	Vacuum Paneer Packing Machine	Standard	2	60
10	Sweet Curd / Plain Curd filling and sealing machine	1000 cups /hr	1	61
11	Ghee Vat	500ltr	1	62
12	Air Compressor	15 HP	1	63
13	CIP System	1KLPH	1	64

SECTION - I



The Odisha State Cooperative Milk Producers' Federation Ltd. D-2, Sahid Nagar, Bhubaneswar-751 007. Ph No- (0674) 2546030/2540273/2540417, Fax No (0674) 2540974

www.omfed.com

TENDER NOTICE

OMFED invites sealed techno-commercial offer in separate envelope from experienced manufacturers / authorized distributors of Dairy Equipments for Supply, installation, testing, commissioning and trial run of dairy equipments at Tirtol Dairy of OMFED.

Tender document can be down loaded from website www.omfed.com from dt.05.01.2024 to dt.29.01.2024 against payment of Rs.5,000/- + 18%GST (or Rs.5,900/-) in shape of Demand Draft drawn in favour OMFED, drawn on any Nationalized bank payable at Bhubaneswar. The tender document should be duly filled & submitted on due date along with the cost of tender paper. Bids with EMD as specified in the tender document shall be received up to 1400 hours on dt.29.01.2024 & shall be opened on the same day at 1500 Hrs. at Omfed Corporate Office, D/2, Sahid Nagar, Bhubaneswar – 751007 in presence of interested bidders. Bids without requisite EMD shall not be considered.

The **corrigendum/amendment** to this notice if required shall be published only in the OMFED web site and will not be published again in newspaper.

OMFED reserves the right to accept or reject any or all the tenders or part thereof without assigning any reason.

MANAGING DIRECTOR

SECTION II INSTRUCTION TO BIDDERS

1.0 GENERAL INFORMATION

1.1 SCOPE OF WORK:-

Supply, installation, testing, commissioning and trial run of dairy equipments at Tirtol Dairy of OMFED.

1.2 LOCATIONS AND AREA

Tirtol Dairy

At- Tirtol, Block- Nuapda, Dist- Jagatsinghpur

1.3 Period of Completion

The period of completion of work including supply, installation, testing, commissioning, trial run and handing over, shall be **120 days** from the date of receipt of work order.

1.4 <u>IMPORTANT NOTE</u>

Period of completion of work is very important for this project. The work has to be carried out strictly as per the work programme.

2.0 Eligibility and Qualification requirements:-

- 2.1 The bidder should have minimum two years' experience in the related field like/supply/installation/Erection & commissioning etc.
- 2.2 Annual Sales turn over should not to be less than 40 lakhs during the financial year 2020-21, 2021-22 & 2022-23.
- 2.3 The bidder should have successfully supplied & commissioned the equipments in the recent past.
- 2.4 The bidder should furnish the supply / commissioning certificate from the concerned client(s).

3.0 Price basis:

3.1 For supply:

The quoted prices for the equipment shall be on FOR destination basis, inclusive of all taxes, including GST, packing & forwarding charges, transportation, insurance and other incidental charges, loading & unloading charges etc. as applicable. The bidder shall, however, provide a break-up of the prices quoted.

Bidders are required to give break up of unit rates & quantities of each & all items to be supplied for the purpose of the contract.

3.2 For erection/installation, testing, commissioning, trial run & handing over:

Bidders shall submit separate rates for complete installation, testing and commissioning, including satisfactory performance trial run for 10 days.

Prices quoted should be on FOR destination basis, inclusive of all taxes & duties, packing & forwarding charges, transportation, insurance and other incidental charges, loading & unloading charges etc. as applicable. The contractor shall be responsible for supply of all sundries / power / fuel as may be required for erection, testing, commissioning & performance trial run for 10 days, including oil and lubricants. However, electrical/ fuel charges during the 10 days period of performance trial run shall be borne by OMFED.

The contractor shall have to create their own storage space for all the equipments & materials and provide watch & ward for it. Insurance of equipments & materials during storage, shifting, installation & testing shall be contractor's responsibility.

4.0 Cost of Bidding

The Bidder shall bear all costs associated with the preparation and submission of its bid, and the Orissa State Cooperative Milk Producers' Federation Limited, hereinafter referred to as "THE OMFED", will in no case be responsible or liable for those costs, regardless of the conduct or outcome of the bidding process.

B. THE BIDDING DOCUMENTS

5.0 CONTENT OF BIDDING DOCUMENTS

- 5.1 The goods required, bidding procedures and contract terms are prescribed in the bidding documents. In addition to the tender notice, the bidding documents include:
 - (a) Instruction to bidders;
 - (b) General Conditions of Contract;
 - (c) Special Conditions of contract (for Erection works);
 - (d) Special Conditions of contract (for Mechanical installation);
 - (e) Special conditions of contract (for Electrical installation);
 - (f) Technical Specifications and schedule of quantities;
 - (g) Form of Agreement;
 - (h) Bid Form;
 - (i) Schedule of Supp. Information;
 - (j) Standard Forms of Bank Guarantees;

5.2 The Bidder is expected to examine all instructions, forms, terms and specifications in the bidding documents. Failure to furnish all information required by the bidding documents or submission of a bid not substantially responsive to the bidding documents in every respect will be at the bidder's risk and may result in the rejection of its bid.

6.0 Clarification of Bidding Documents

A prospective Bidder requiring any clarification of the Bidding Documents may notify the OMFED in writing or by Fax or Cable at the OMFED'S mailing address indicated in this document. The OMFED will respond in writing to any request for clarification of the bidding Documents which it receives not later than 15 days prior to the deadline for the submission of bids prescribed by the OMFED. Written copies of the OMFED'S response (including an explanation of the query but without identifying the source of inquiry) will be sent to all prospective Bidders which have received the bidding Documents, and will be attached to the Bidding Documents sold subsequently.

7.0 Amendment of Bidding Documents

- 7.1 At any time prior to the deadline for submission of bids, the OMFED may, for any reason, whether at its own initiative or in response to a clarification requested by a prospective Bidder, modify the Bidding Documents by amendment.
- 7.2 The amendment will be notified in writing or by Fax or cable to all prospective Bidders, which have received the Bidding Documents and will be binding on them. The amendment will be attached to the bidding documents sold subsequently.
- 7.3 In order to afford prospective Bidders reasonable time in which to take the amendment into account in preparing their bids, the OMFED may, at its discretion, extend the deadline for the submission of bids.

8.0 PREPARATION OF BIDS

8.1 DOCUMENTS TO BE SUBMITTED IN THE TECHNICAL BID:

- Audited profit & loss account statement for the year 2020-21, 2021-22 & 2022-23.
- Proof of sales turn over for last three consecutive years.
- Copy of IT return for the financial year 2020-21, 2021-22 & 2022-23.
- GST Number.
- GSTIN / PAN No.
- Purchase order copy and commissioning report / performance report in support of supply
 of said machineries and installation during last three years.
- Cost of tender paper in shape of Demand draft only.
- Demand draft towards EMD as specified at clause no.13.0 (page-10) in the tender document.

8.2 DOCUMENTS TO BE SUBMITTED IN THE COMMERICIAL BID:

- The original bidding document as downloaded by the bidder should be signed & sealed in each page by the bidder as a token of having read, understood & accepted the contents, therein.
- Filled in Commercial bid with Cost of said equipments with details along with installation & Commissioning charges.
- The rate shall include freight, packing, forwarding inclusive of GST / all taxes etc.
- The bid form and schedule of quantities, provided in the bidding document, completed in accordance with clauses 09 and 10.
- Documentary evidence established in accordance with Clause 11 that the bidder is eligible to bid and is qualified to perform the contract if its bid is accepted.
- The rate shall include freight, packing, forwarding all taxes including service taxes & duties and including CESS.

9.0 Bid form

The Bidder shall complete the bid Form and the schedule of quantities furnished in the Bidding Documents, indicating for the goods to be supplied, a brief description of the goods, quantity and prices.

10.0 Bid Prices

10.1 The bidder shall indicate in the schedule of quantities, provided in this document, the unit prices and total Bid prices of the goods it proposes to supply under the Contract, on FOR destination basis, inclusive of all taxes & duties, packing & forwarding charges, transportation, insurance and other incidental charges, loading & unloading charges etc. as applicable. It is not mandatory on the part of OMFED to procure all the items and quantity as mentioned in the bills of quantity.

10.2 <u>Bidders shall provide the break-up of their offered prices separately in the following manner:</u>

- (i) The price of the goods, quoted ex-factory, ex-showroom, ex-warehouse or off-theshelf, as applicable, including all duties / GST and other taxes already paid or payable:
- On the components and raw material used in the manufacture or assembly of goods quoted ex-factory;

Or

- The price of the goods, quoted ex-factory, ex-showroom, ex-warehouse or off-the-shelf, as applicable, including all duties and sales other taxes already paid or payable on the imported goods of foreign origin quoted ex-showroom, ex-warehouse or off-the-shelf.
- (ii) Any other taxes applicable in India which will be payable on the goods if this contract is awarded;

- (iii) Charges for packing and forwarding, inland transportation, insurance and other costs incidental to delivery of the goods to their final destination; and
- (iv) The cost of all incidental services required under the contract.
- 10.3 The bidder's separation of price components in accordance with Para. 10.2 above will be solely for the purpose of facilitating the comparison of bids by the OMFED.

10.4 Fixed Price

Prices quoted by the Bidder shall be fixed during the Bidder's performance of the contract and not subject to variation on any account. A bid submitted with an adjustable price basis for such goods and services will be treated as non-responsive and rejected, pursuant to clause 23.

11.0 <u>Documents Establishing Bidders' Eligibility and Qualifications</u>

- 11.1 The Bidder shall furnish, as part of its bid, documents establishing the bidder's eligibility to bid and its qualifications to perform the contract if its bid is accepted. The bidder should also give information in the format attached to the Bid document.
- 11.2 The documentary evidence of the Bidder's qualification to perform the contract if its bid is accepted, shall establish to the OMFED'S satisfaction:
 - a) That, in the case of a bidder offering to supply goods under the contract which the bidder did not manufacture or otherwise produce, the Bidder has been duly authorized by the goods' manufacturer or producer to supply the goods.
 - b) That the bidder has the financial, technical and production capability necessary to perform the contract. To this end, all bids submitted shall include the following information along with Schedule-I and schedule-II under Section VIII:
 - i) Copies of original documents defining the constitution or legal status, place of registration and principal place of business of the company or firm or partnership etc.
 - ii) Details of experience and past performance of the bidder on equipment offered and on those of similar nature within the past 3 years and details of current contracts in hand and other commitments;
 - iii) Major items of plant and equipment available/ installed in the Bidder's factory premises;
 - iv) Qualification and experience of key personnel for successful execution of the contract;
 - v) Reports on financial standing of the bidder such as profit and loss statements, balance sheets and auditor's report of the past three years, bankers certificates etc;
 - vi) Information regarding any current litigation in which the bidder is involved.

12.0 <u>Documents Establishing Goods' Eligibility and Conformity to Bidding Documents</u>

12.1 The bidder shall furnish, as part of its bid, documents establishing the eligibility and conformity to the Bidding Documents of all goods and services, which the bidder proposes to supply under the contract.

- 12.2 The documentary evidence of the goods and services conformity to the bidding documents may be in the form of literature, drawing and data, and shall furnish:
 - (a) A detailed description of the goods' essential technical and performance characteristics.
 - (b) A list giving full particulars, including available sources and current prices, of all spare parts, special tools, etc. necessary for the proper and continuing functioning of the goods for a period of two years, following commencement of the goods' use by the OMFED: and
 - (c) A clause-by-clause commentary on the OMFED'S technical specification demonstrating the goods' and services' substantial responsiveness to those specifications or a statement of deviations and exceptions to the provisions of the technical specification.
- 12.3 For purposes of the commentary to be furnished pursuant to Clause12.2 (c) above, the Bidder shall note that standards for workmanship, material and equipment, and references to brand names or catalogue numbers designated by the OMFED in its Technical specifications are intended to be descriptive only and not restrictive. The Bidder may substitute alternative standards, brand names and/ or catalogue numbers in its bid, provided that it demonstrates to the OMFED'S satisfaction that the substitutions are substantially equivalent or superior to those designated in the Technical specifications.

13.0 <u>Bid Security (Earnest Money Deposit)</u>

13.1 Pursuant to clause 8, the Bidder shall furnish, as part of its bid, **bid security as furnished below.**

SI No	Name of equipment	Capacity	Quantity (nos)	EMD (Rs.)
1	Online Milk Pasteuriser	5KLPH	1	20,000/-
2	Online Milk Homogeniser	5KLPH	1	20,000/-
3	Online Cream Separator	5KLPH	1	10,000/-
4	Milk Can Washer	600 Cans/hr.	1	20,000/-
5	Milk Silo	10 KL	1	8,000/-
6	Two Stage PHE	1KLPH	1	2,000/-
7	Multi Purpose Vat	1 KL	1	6,000/-
8	Khoa / Rabidi Pan	240 Ltr	1	6,000/-
9	Vacuum Paneer Packing Machine	Standard	2	16,000/-
10	Sweet Curd / Plain Curd filling and sealing machine	1000 cups /hr	1	4,000/-
11	Ghee Vat	500ltr	1	4,000/-
12	Air Compressor	15 HP	1	10,000/-
13	CIP System	1KLPH	1	20,000/-

- 13.2 The bid security is required to protect the OMFED against the risk of bidder's conduct, which would warrant the security's forfeiture, pursuant to para.13.7.
- 13.3 The bid security shall be in one of the following forms:
- (a) A Bank guarantee issued by a Nationalised bank located in India in the form provided in the Bidding Documents, and valid for 30 days beyond the validity of the bid, or

- (b) A demand draft in favour of ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD., Payable at Bhubaneswar.
- 13.4 Any bid not secured in accordance with para's. 13.1 and 13.3 will be rejected by the OMFED as non-responsive.
- 13.5 Unsuccessful bidder's bid security will be discharged/returned as promptly as possible but not later than 30 days after the expiration of the period of bid validity.
- 13.6 The successful Bidder's bid security will be discharged upon the bidders executing the agreement, pursuant to clause 32, and furnishing the performance security, pursuant to clause 34.
- 13.7 The bid security may be forfeited:
- (a) If a bidder withdraws its bid during the period of bid validity specified by the bidder on the bid form; or
- (b) In the case of successful bidder, if the bidder fails;
 - (i) To sign the contract in accordance with clause 31

Or

(ii)To furnish performance security in accordance with clause 32.

14.0 Period of validity of bids

- 14.1 Bids shall remain valid for 01 year after the date of bid opening, stated in the cover page/ tender notice. A bid valid for a shorter period may be rejected by the OMFED as nonresponsive.
- 14.2 In exceptional circumstance, the OMFED may solicit the bidders' consent to an extension of the period of validity. The request and the responses thereto shall be made in writing or by Cable or Fax. The bid security provided under clause-13 shall also be suitably extended. A bidder may refuse the request without forfeiting its bid security. A bidder granting the request will not be required nor permitted to modify its bid.

15.0 Format and signing of bid

- The original bid shall be typed or written in indelible ink and shall be signed by the bidder or a person or persons duly authorised to bind the bidder to the contract. The latter authorization shall be indicated by written power-of-attorney accompanying the bid. All pages of the bid, except for unammended printed literature, shall be initialed by the person or persons signing the bid.
- 15.2 The bid shall contain no interlineations, erasures or overwriting except as necessary to correct errors made by the bidder, in which case corrections shall be initialed by the person or persons signing the bid.

D. Submission of bids

16.0 Sealing and marking of bids

- 16.1 The bidders shall seal the original bidding document, along with all relevant documents & drawings, in an envelope.
- 16.2 The envelope shall:
 - (a) Be addressed to the OMFED at the following address: ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD., D-2, Sahid Nagar, Bhubaneswar 751007.
 - (b) Bear the Tender Reference No., Name of work & Date of opening.

- (c) Indicate the name and address of the bidder.
- 16.3 If the outer envelope is not sealed and marked as required by Para. 16.2, The OMFED will assume no responsibility for the bid's misplacement or premature opening. A bid opened prematurely for this cause will be rejected by the OMFED.
- 16.4 The bidders shall submit the "Eligibility and post-qualification application "along with the bid.

17.0 Deadline for submission of bids

- 17.1 Bids must be received by the OMFED at the address specified in cover page / tender notice not later than the date and time specified for receipt of the bids as indicated in cover page / tender notice.
- 17.2 The OMFED may, at its discretion, extend this deadline for the submission of bids by amending the bidding documents in accordance with Para 7, above in which case all rights and obligations of the OMFED and bidders previously subject to the deadline will thereafter be subject to the deadline as extended.

18. Late bids

Bids received after the deadline for submission of bids will be rejected or returned unopened to the bidder. OMFED shall not bear any responsibility for late delivery of bids submitted by post.

19. Modification and withdrawal of bids

- 19.1 The bidder may modify or withdraw its bid after the bid's submission, provided that written notice of the modification or withdrawal is received by the OMFED prior to the deadline prescribed for submission of bids.
- 19.2 The bidder's modification or withdrawal notice shall be prepared, sealed, marked and submitted in accordance with the provisions of Para 16. A withdrawal notice may also be sent by Fax or cable but followed by a signed confirmation copy, post marked not later than the deadline for submission of bids.
- 19.3 No bid may be withdrawn in the interval between the deadline for submission of bids and the expiration of the period of bid validity. Withdrawal of a bid during this interval shall result in the bidder's forfeiture of its bid security.

E. <u>BID OPENING AND EVALUATION</u>

20.0 Opening of Bids by OMFED

- 20.1 The OMFED will open bids, in the presence of bidders' representatives who choose to attend, at the time and date specified in the Tender notice, at the office of the ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD., D-2, Sahid Nagar, Bhubaneswar-751007, Orissa, India. The Bidders representatives who are present shall sign attendance sheet evidencing their presence during the bid opening.
- 20.2 The Bidders' names, bid prices, modifications, bid withdrawals and the presence or absence of the requisite bid security and such other details as the OMFED, at its discretion, may consider appropriate will be announced at the opening.

21.0 Clarification of bids

21.1 To assist in the examination, evaluation and comparison of bids the OMFED may, at its discretion, ask the Bidders for a clarification of its bid. The request for clarification and the response shall be in writing.

22.0 Preliminary Examination

- The OMFED will examine the bids to determine whether they are complete, whether any computational errors have been made, whether required sureties have been furnished, whether the documents have been properly signed, and whether the bids are generally in order.
- 22.2 Arithmetical errors will be rectified on the following basis. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail. If there is a discrepancy between words and figures, the amount in words will prevail. The total price shall be corrected accordingly. If the bidder does not accept the correction of the errors, its bid will be rejected.
- 22.3 Prior to the detailed evaluation, pursuant to Para 23, the OMFED will determine the substantial responsiveness of each bid to the bidding documents. For purposes of these clauses, a substantially responsive bid is one, which conforms to all the terms and conditions of the bidding documents without material deviations. The OMFED'S determination of a bid's responsiveness is to be based on the contents of the bid itself.
- 22.4 A bid determined as not substantially responsive will be rejected by the OMFED.
- 22.5 The OMFED may waive any minor informality or non-conformity or irregularity in a bid, which does not constitute a material deviation, provided such waiver, does not prejudice or affect the relative ranking of the Bidder.

23.0 Evaluation and Comparison of Bids

- 23.1 The OMFED will evaluate and compare the bids previously determined to be substantially responsive, pursuant to Para 22. However, bidders are allowed the option to offer discounts. The discounts will be taken into account in the evaluation of bids so as to determine the bid offering the lowest evaluated cost for the OMFED in deciding award.
- 23.2 The comparison shall be on FOR site basis, (such price to include all costs as well as duties and taxes paid or payable on components and raw material incorporated or to be incorporated in the goods and GST payable on finished goods offered) as well as on the cost of installation, testing, commissioning & performing 30 days trial run.
- 23.3 The OMFED'S evaluation of a bid will take into account, in addition to the bid price and the cost of services including installation, testing, commissioning, performance trial run & handing over, the following factors:
 - (a) Cost of inland transportation, insurance and other costs incidental to delivery of the goods to their final destination including excise duty;
 - (b) Delivery schedule offered in the bid;
 - (c) The cost of components, spare parts and service;
 The availability in India of spare parts and after sales services for the equipment offered in the bid;
 - (d) Deviation in payment schedule from that specified in the special conditions of contract:
 - (e) The quality and adaptability of the equipment offered.

24.0 Contacting the OMFED

- 24.1 No Bidder shall contact the OMFED on any matter relating to its bid, from the time of the bid opening to the time the contract is awarded, unless invited by the OMFED for discussions / clarifications.
- 24.2 Any effort by a bidder to influence the OMFED in the OMFED'S bid evaluation, bid comparison or contract award decisions shall result in the rejection of the Bidder's bid.

F. AWARD OF CONTRACT

25.0 Post-qualification

- 25.1 In the absence of pre-qualification, the OMFED will determine to its satisfaction whether the bidder selected as having submitted the lowest evaluated responsive bid is qualified to satisfactorily perform the contract.
- 25.2 The determination will take into account the Bidder's financial, technical and production capabilities. It will be based upon an examination of the documentary evidence of the bidder's qualifications submitted by the bidder, as well as such other information as the OMFED deems necessary and appropriate including details of experience and records of past performance. The OMFED may also inspect the works of the bidder to satisfy itself regarding the capability of the bidder.
- 25.3 An affirmative determination will be a prerequisite for award of the contract to the Bidder. A negative determination will result in rejection of the Bidder's bid, in which event; the OMFED will proceed to the next lowest evaluated bid to make a similar determination of that Bidder's capabilities to perform satisfactorily.

26.0 AWARD CRITERIA

The OMFED will consider award of contract to the successful bidder whose bid have been determined to be substantially responsive and have been determined as the lowest evaluated bid, pursuant to Para 23 and 25 & who is determined to be qualified to satisfactorily perform the contract.

The composite price towards the cost of the equipment and Annual Maintenance contract shall be considered to arrive at the lowest bidder price.

27.0 OMFED'S RIGHT TO VARY QUANTITES AT TIME OF AWARD.

The OMFED reserves the right to increase or decrease the quantity of goods and services specified in the schedule of requirements without any change in unit price or other terms and conditions.

28.0 OMFED'S Right to Accept Any Bid and to reject Any or All Bids

The OMFED reserves the right to accept or reject any bid, and to annul the bidding process and reject all bids at any time prior to award of contract, without thereby incurring any liability to the affected bidder or bidders or any obligation to inform the affected bidder or bidders of the grounds for the OMFED'S action.

29.0 Notification of Award

- 29.1 Within the period of bid validity, the OMFED will notify the successful bidder in writing by registered letter or by cable/ telex/ fax, (to be confirmed in writing by registered letter) that its bid has been accepted.
- 29.2 The notification of award will constitute the formation of the contract.
- 29.3 Upon the successful bidder's furnishing of performance security, the OMFED will promptly notify each unsuccessful bidder and will discharge its bid security.

30.0 Signing of Agreement

Within 15 days of receipt of the notification of award, the successful bidder shall prepare & sign the agreement, in the format provided in this bidding document, and send the same to the OMFED along with a duplicate copy. The original contract form shall be retained by the OMFED, & a duplicate copy of the same shall be sent to the contractor, after it has been signed and dated.

31.0 Performance Security

- 31.1 Within 15 days of receipt of the notification of award from the OMFED, the successful bidder shall furnish the performance security deposit in accordance with clause 6 of the general conditions of contract, either in the form of a Bank guarantee valid for **15 months** from the expected date of completion of contract (as per the performance security form provided in the bidding document) or in the form of demand draft of required value in favour of OMFED, payable at Bhubaneswar.
- 31.2 Failure of the successful bidder to comply with the requirement of Para 30 or Para 31 shall constitute sufficient grounds for the annulment of the award and forfeiture of the bid security, in which event the OMFED may make the award to the next lowest evaluated bidder or call for new bids.

32.0 IMPORT LICENCE

No import license shall be provided by the OMFED for goods offered against this bid.

SECTION -III.

GENERAL CONDITIONS OF CONTRACT

1. Definitions

- 1.1 In this contract, the following terms shall be interpreted as indicated.
- (a) "The contract" means the agreement entered into between the OMFED and the contractor, as recorded in the contract form signed by the parties, including the notification of award, all attachments and appendices thereto and all documents incorporated by reference therein;
- (b) "The contract price" means the price payable to the contractor under the contract for the full and proper performance of its contractual obligations;
- (c) "The goods" means all of the equipment, machinery, and/or other materials which the contractor is required to supply to the OMFED under the contract;
- (d) "Services" means services ancillary to the supply of the goods, such as transportation and insurance, and any other incidental services, such as installation, testing, commissioning, performance trial run for 30 days, provision of technical assistance, training and other such obligations of the contractor covered under the contract;
- (e) The OMFED" means the organization purchasing the goods and services under the contract i.e. ORISSA STATE COOPERATIVE MILK PRODUCERS' FEDERATION LTD.
- (f) "The contractor" means the individual(s) or firm(s) supplying the goods under this contract i.e., with which an agreement has been signed by the OMFED for supply of goods & services required elsewhere in this document.

2. APPLICATION

These general conditions shall apply to the extent that they are not superseded by provisions in other parts of the contract.

3. STANDARDS

The quality standard with ISI / BIS / any other recognized standard shall be preferred.

The goods supplied under this contract shall conform to the standards mentioned in the technical specifications, and, when no applicable standard is mentioned, to the Indian standards.

Wherever reference is made in the contract to the respective standards and codes in accordance with which goods and materials are to be furnished, and work is to be performed or tested, the provisions of the latest current edition or revision of the relevant standards and codes in effect on the date of signing of agreement shall apply, unless otherwise expressly set forth in the contract.

4. Use of Contract and Information

- 4.1 The contractor shall not, without the OMFED'S prior written consent, disclose the contract, or any provision thereof, or any specification, plan, drawing, pattern, sample or information furnished by or on behalf of the OMFED in connection therewith, to any person other than a person employed by the contractor in the performance of the contract. Disclosure to any such employed person shall be made in confidence and shall extend only so far as may be necessary for purposes of such performance.
- 4.2 The contractor shall not, without the OMFED'S prior written consent, make use of any document or information enumerated in para.4.1 except for purposes of performing the contract.
- 4.3 Any document, other than the contract itself, enumerated in Para. 4.1 shall remain the property of the OMFED and shall be returned (in all copies) to the OMFED on completion of the contractor's performance under the contract if so required by the OMFED.

5. PATENT RIGHTS

The contractor shall indemnify the OMFED against all third-party claims of infringement of patent, trademark or industrial design rights arising from use of the goods/services or any part thereof in India.

6.0 PERFORMANCE SECURITY

- 6.1 Within 15 days of the contractor's receipt of notification of award of the contract, the contractor shall furnish performance security to the OMFED in the amount of 10% of the contract value, in accordance to clause 31 of the instruction to bidders.
- 6.2 The proceeds of the performance security shall be payable to the OMFED as compensation for any loss resulting from the contractor's failure to complete its obligations under the contract.
- 6.3 The performance security shall be denominated in Indian rupees and shall be in the following form:
- a) A Bank guarantee, issued by a Nationalised Bank in India, and in the form provided in the bidding documents.
- b) Demand draft in favour of "Orissa State Co-operative Milk Producers' Federation Limited" payable at Bhubaneswar.
 - Such Bank guarantee shall be valid upto three months after the expiry of the warranty / guarantee period.
- 6.4 The performance security will be discharged by the OMFED and returned to the contractor not later than 90 days following the date of completion of the contractor's performance obligations, including any warranty / guarantee obligations, under the contract.
- 6.5 No interest shall be paid on the performance security deposit by the OMFED.

7. <u>Inspection and Tests</u>

- 7.1 The OMFED or its representative shall have the right to inspect and/or test the goods to confirm their conformity to the contract. The Technical Specifications shall specify what inspections and tests the OMFED shall notify the contractor in writing of the identity of any representatives, if retained for these purposes.
- 7.2 The inspection of the goods shall be carried out to check whether the goods are in conformity with the technical specifications and shall be in line with the inspection/test procedures laid down in the schedule of specifications and the contract conditions.
- 7.3 The inspections and tests may be conducted on the premises of the contractor or its subcontractor(s) / at point of delivery and/or at the good's final destination. Where conducted on the premises of the contractor or its subcontractor(s) / all reasonable facilities and assistance including access to drawings and production data, shall be furnished to the inspectors at no charge to the OMFED. In case of any defects or deficiency notified by the OMFED'S inspection authority, the contractor will rectify and make good the same without delay and not proceed further processing of such items(s) of goods without obtaining approval from the inspection authority.
- 7.4 Should any inspected or tested goods fail to conform to the specifications/ the OMFED may reject them and the contractor shall either replace the rejected goods or make all alterations necessary to meet specification requirements free of cost to the OMFED.
- 7.5 The OMFED'S right to inspect, test and, where necessary, reject the goods after the goods' arrival at destination shall in no way be limited or waived by reason of the goods having previously been inspected, tested and passed by the OMFED or its representative.
- 7.6 Nothing in clause 7 shall in any way release the contractor from any warranty or other obligations under this contract.

8. Packing and Marking

- 8.1 The contractor shall provide such packing of the goods as is required to prevent their damage or deterioration during transit to their final destination as indicated in the contract. The packing shall be sufficient to withstand, without limitation, rough handing during transit and exposure to temperature, salt and precipitation during transit and open storage. Packing case size and weights shall take into consideration, where appropriate, the remoteness of the goods' final destination and the absence of heavy handing facilities at all points in transit & destination.
- 8.2 The packing, marking and documents within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the contract, required by law, and, subject to clause 18, in any subsequent instructions ordered by the OMFED.

- 8.3 Each package shall be marked to indicate:
 - a) Name of the contractor
 - b) Details of items in the package
 - c) Name of the consignee
 - d) Order number
 - e) Gross/net and tare weights of the item
 - f) Destination

9. Delivery and documents

- 9.1 Delivery of the goods shall be made by the contractor for destination, by road.
- 9.2 The following documents shall be provided by the contractor / contractor:

Original and three copies of:

- (I) The contractor's invoice showing order no. Goods description, quantity, unit price, total amount;
- (ii) Delivery note/packing list/lorry receipt;
- (iii) Manufacturer's/contractor's guarantee certificate;
- (iv) Inspection certificate issued by the nominated inspection agency, and the contractor's factory inspection report;
- (v) Insurance policy;
- (vi) Excise gate pass/octroi receipts, wherever applicable, duly sealed indicating payments made; and
- (vii) Any other document evidencing payment of statutory levies.

Note: The nomenclature used for the item description in the invoice/s, packing list/s and delivery note/s etc. should be identical to that used in the order. The dispatch particulars including name of transporter, LR no. and date should also be mentioned in the invoice/s.

10. <u>Insurance</u>:

10.1 For supply of equipments:

The manufacturer shall have to arrange all transit risk insurance warehouse to warehouse basis, including strike clauses, for an amount equal to 110 % of the FOR destination value of the Goods, valid for a period of not less than 3 months after the expected date of arrival of Goods at destination.

In the event of any damage to/loss of consignment in transit, it will be your responsibility to lodge necessary claims with the carriers/ underwriters and pursue them till settlement. Since the insurance policy will be in our name, if required, we shall give you necessary authorisation letter authorizing you to lodge and pursue claims on our behalf with the carriers/ underwriters. Also you shall have to make good the losses/ damages occurred in transit by making replacement /payment to us in the first instance and if claims are settled by the underwriters and any amounts are realized by us, the amounts thus realized in settlement of claims shall be reimbursed to you. In other words, the prima

facie responsibility rests on you for getting compensation of the damage/losses incurred if any, due to all transit hazards.

10.2 **During storage at site:**

The contractor shall arrange for insurance of all items stored/ received at the site including the items of supply covered under this contract & the contractor shall furnish necessary details of such insurance to the OMFED, on demand. Any default on the part of the contractor due to which any item does not get covered under insurance; the consequential losses shall be charged to the contractor.

The contractor shall arrange for insurance of all the items brought by him to the site for use during the execution of the contract, till handing over of the complete job.

11. <u>Transportation</u>

The contractor is required to deliver the Goods FOR Destination, by road. Transport of the goods to the destination shall be arranged through a reputed and Bank approved transporter having local offices at destination and Bhubaneswar, and shall be paid for by the contractor.

12. Incidental services

- 12.1 The contractor is required to provide the following services:
 - a) Performance of on-site assembly, installation, hooking-up to existing system, Startup, testing, commissioning, performance trial run for a period of 30 days and handing over of the supplied goods;
 - b) Furnishing of tools & tackles required for assembly and maintenance of the supplied goods;
 - c) Furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied goods;
 - d) Operation, maintenance and repair of the supplied goods for a period of 30 days, provided that this service shall not relieve the contractor of any warranty obligations under this contract; and
 - e) Conduct of training of the OMFED'S personnel, on-site, in assembly, start-up operation, maintenance and repair of the supplied goods, if required.
- 12.2 Prices charged by the contractor for the preceding incidental services are to be included in the price of the contract.

13. Spare parts

- 13.1 The contractor may be required to provide any or all of the following materials and notifications pertaining to spare parts manufactured or distributed by the contractor:
 - Such spare parts as the OMFED may elect to purchase from the contractor, provided that this election shall not relieve the contractor of any warranty obligations under the contract; and
 - b) In the event of termination of production of the spare parts:
 - (i) Advance notification to the OMFED of the pending termination, in sufficient time to permit the OMFED to procure its needed requirements; and
 - (ii) Following such termination, furnishing at no cost to the OMFED, the blueprints, drawings and specifications of the spare parts, if and when requested.
- 13.2 Contractors shall carry sufficient inventories to assure ex-stock supply of consumable spares such as gaskets, plugs, washers, belts, etc. other spare parts and components shall be supplied as promptly as possible but in any case within six months of placement of order.
- 13.3 The obligation of contractor stated in Para 13.1 shall continue even after expiry of the contract.

14. Warranty / guarantee

- 14.1 The contractor warrants that the goods supplied under the contract are new, unused, of the most recent or current models and incorporate all recent improvements in design and materials unless provided otherwise in the contract. The contractor further warrants that the goods supplied under this contract shall have no defect arising from design, material of workmanship or from any act or omission of the contractor that may develop under normal use of the supplied goods in the conditions. The contractor also guarantees that the goods supplied shall perform satisfactorily as per the designed/rated/ installed capacity as provided for in the contract.
- 14.2 This warranty / guarantee shall remain valid for 12 months after the goods, or any portion thereof as the case may be, have been delivered, commissioned & handed over to the OMFED after the performance of 30 days trial run period.
- 14.3 The OMFED shall promptly notify the contractor in writing of any claims arising under this warranty.
- 14.4 Upon receipt of such notice, the contractor shall, with all reasonable speed, repair or replace the defective goods or parts thereof, without costs to the OMFED.
- 14.5 If the contractor, having been notified, fails to remedy the defects(s) within a period of 30 days, the OMFED may proceed to take such remedial action as may be necessary, at the contractor's risk and expense and without prejudice to any other rights which the OMFED may have against the contractor under the contract.

14.6 This warranty/ guarantee shall not cover any damage/s resulting from normal wear and tear or improper handing by the OMFED or his authorised representatives.

15. <u>Terms of payment For Mechanical equipments.</u>

15.1 For Supply of Equipment.

80% Payment after safe arrival of material at site.

Balance payment after successful commissioning and handing over.

All payments are subject to deduction of statutory dues as applicable.

PSD @10% of the order value shall be retained & shall be released after one year from the date of handing over subject to satisfactory performance. PSD can be released during retention period against equivalent amount of Bank guarantee.

However, if the supply of erection materials is within the scope of OMFED, in such case the client shall refund the PSD against BG subject to claim of the bidder. It is mandatory on the part of the bidder to arrange for commissioning, trial run for the equipment supplied after inter connection of pipelines etc failing which the PSD shall be retained by the client, till the successful commissioning by the bidder.

15.2 For Erection component.

Payment in full shall be released after successful installation / commissioning.

16. Fixed prices

Prices charged by the contractor for goods delivered and services performed under the contract shall not, vary from the prices quoted by the contractor in its bid.

17. Change orders

- 17.1 The OMFED may, at any time, by a written order given to the contractor, make changes within the general scope of the contract in any one or more of the following:
- (a) Drawings, designs or specifications, where goods to be furnished under the contract are to be specifically manufactured for the OMFED;
- (b) The method of shipment or packing;
- (c) The place of delivery; or
- (d) The services to be provided by the contractor.
- 17.2 If any such change causes an increase or decrease in the cost of, or the time required for, the contractor's performance of any part of the work under the contract, whether changed or not changed by the order, an equitable adjustment shall be made in the contract price or delivery schedule, provided that such claims by contractor are reasonable & to the satisfaction of the OMFED. Any claims by the contractor for adjustment under this clause must be asserted within thirty (30) days from the date of the contractor's receipt of the OMFED's change order.

18. Contract Amendment

Subject to clause 17, no variation in or modification of the terms of the contract shall be made except by written amendment signed by the OMFED.

19. Assignment

The contractor shall not assign, in whole or in part, its obligations to perform under the contract, except with the OMFED'S prior written consent.

20. <u>Subcontracts</u>

The contractor shall notify the OMFED in writing of all subcontracts awarded under the contract if not already specified in his bid, such notification, in his original bid or later, shall not relived the contractor from any liability or obligation under the contract.

21.0 Delays in the contractor's performance

- 21.1 Deliveries in the goods and performance of services shall be made by the contractor in accordance with the time schedule specified by the OMFED, in Section –I of the bidding documents.
- 21.2 An unexcused delay by the contractor in the performance of its delivery obligations shall render the contractor liable to any or all of the following sanctions: forfeiture of its performance security, imposition of liquidated damages, and/ or termination of the contract for default.
- 21.3 If at any time during performance of the contract, the contractor or its subcontractor(s) should encounter conditions impending timely delivery of the goods and performance of services. The contractor shall promptly notify the OMFED in writing of the fact of the delay, its likely duration and its cause (s). As soon as practicable after receipt of the contractor's notice, the OMFED shall evaluate the situation and may at its discretion extend the contractor's time for performance, in which case the extension shall be notified to the contractor by amendment of the contract.

22.0 <u>Time for completion</u>

Subject to any requirement in the contract as to completion of any section of the works before completion of the whole, the whole of the works shall be completed, within the stipulated time stated in section–II of the bidding documents or such extended time as may be allowed under clause 23 hereof.

23.0 Extension of Time of Completion

Should the amount of extra or additional work of any kind or any cause of delay referred to in these conditions, or exceptional adverse climatic conditions, or other special circumstances of any kind whatsoever which may occur, other than through a default of the contractor, be such as fairly to entitle the contractor to an extension of time for the completion of the works. OMFED shall determine the amount of such extension and shall notify the contractor accordingly. Provided that the OMFED is not bound to take in account any extra or additional works or other special circumstances unless the contractor has within thirty days after such work has been commenced, or such circumstances have arisen, or as soon thereafter as is practicable, submitted to the engineer full and detailed particulars of any extension of time to which he may consider himself entitled in order that submission may be investigated at the time.

24.0 Penalty for Delay

- 24.1 If the contractor shall fail to achieve completion of the works within the specified time, then the contractor shall pay to the OMFED the sum at the rate of 0.5 % (half percent) of the total value of work done under the contract, as a penalty, for every week or part of the week which shall elapse, between the time prescribed & the date of certified completion of the work. The OMFED may without prejudice to any other method of recovery, deduct the amount of such penalty from any payment in its hands, due or which may become due to the contractor. The payment or deduction of such penalty shall not relieve the contractor from obligations to complete the works, or from any other of his obligations and liabilities under the contract.
- 24.2 The aggregate maximum of the penalty for delay payable to the OMFED under this clause shall be subject to a maximum of 10 % of the total value of work.
- 24.3 The criteria for deriving the penalty for delay shall be the actual value of works executed and the amended time of completion.
- 24.4 Any incremental taxes and levies due to the delay in the performance of the contract by the contractor shall be to the contractor's account.

25. Termination for default

- 25.1 The OMFED may, without prejudice to any other remedy for breach of contract, by written notice of default sent to the contractor, terminate the contract in whole or in part,
- (a) If the contractor fails to delivery an or all the goods within the time period (s) specified in the contract, or any extension thereof granted by the OMFED pursuant to clause 17, 21, & 22:

Or

- (b) If the contractor fails to perform any other obligation(s) under the contract.
- 25.2 In the event the OMFED terminates the contract in whole or in part, pursuant to Para. 25.1, the OMFED may procure, upon such terms and in such manner, as it deems appropriate, goods similar to those undelivered, and the contractor shall be liable to the OMFED for any excess costs for such similar goods. However, the contractor shall continue performance of the contract to the extent not terminated.
- 25.3 Consequent to such termination of contract, the OMFED shall recover the advance paid, if any, to the contractor along with interest @ 18 % per annum compounded quarterly on the last day of March, June, September and December on the advance paid for the entire period for which the advance was retained by the contractor.

26. Force Majeure

26.1 Not withstanding the provisions of clauses hereof, the contractor shall not be liable for forfeiture of its performance security, liquidated damages or termination for default, if and to the extend that, its delay in performance or other failure to perform its obligations under the contract is the result of an event of force majeure.

- 26.2 For purposes of this clause, "force majeure" means an event beyond the control of the contractor and not involving the contractor's fault or negligence and not foreseeable. Such events may include, but are not restricted to, acts of the OMFED either in its sovereign or contractual capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions and freight embargoes.
- 26.3 If a force majeure situation arises, the contractor shall notify the OMFED in writing of such condition and the cause thereof, within 7 days. Unless otherwise directed by the OMFED in writing, the contractor shall continue to perform its obligations under the contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the force majeure event.

27.0 <u>Termination for Insolvency</u>

The OMFED may at any time terminate the contract by giving written notice to the contractor, without compensation to the contractor, if:

- (a) The contractor becomes bankrupt or otherwise insolvent,
- (b) The contractor being a company is wound up voluntarily by the order of a court receiver, liquidator or manager appointed on behalf of the debenture holders or circumstances shall have arisen which entitle the court or debenture holders to appoint a receiver, liquidator or a manager,

Provided that such termination will not prejudice or affect any right of action or remedy which has accrued or will accrue thereafter to the OMFED.

28.0 <u>Termination for Convenience</u>

- The OMFED, may by written notice sent to the contractor, terminate the contractor, in whole or in part, at any time for its convenience. The notice of termination shall specify that termination is of the OMFED'S convenience, the extent to which performance of work under the contract is terminated, and the date upon which such termination becomes effective.
- 28.2 The goods that are complete and ready for shipment within 30 days after the contractor's receipt of notice of termination shall be purchased by the OMFED at the contract terms and prices. For the remaining goods, the OMFED may elect:
- (a) To have any portion completed and delivered at the contract terms and prices; and /or
- (b) To cancel the remainder and pay to the contractor an agreed amount for partially completed goods and for material and parts previously procured by the contractor.

29.0 Settlements of Disputes

29.1 If the contractor considers any work demanded of him to be outside the requirements of the contract, or considers any drawings, record or ruling of the engineer on any matter in connection with or arising out of the contract or the carrying out of the work to be unacceptable, he shall promptly ask the engineer in written instructions or decision. There upon the engineer shall give his written instructions or decision within a period of fifteen days of such request.

- 29.2 Upon the receipt of the written instructions or decisions the contractor shall promptly proceed without delay to comply with such instructions or decisions.
- 29.3 If the engineer fails to give his instructions or decisions in writing within a period of fifteen days after being requested, or if the contractor is dissatisfied with the instructions and decisions, he shall appeal to the OMFED, which shall afford an opportunity to the contractor to be heard and to offer an evidence in support of his appeal. The OMFED shall give a decision within a period of thirty days after the contractor has given the said evidence in support of his appeal.
- 29.4 If the contractor is dissatisfied with this decision, the contractor within a period of thirty days from the receipt of the decisions shall indicate his intension to refer the dispute to arbitration, failing which the said decision shall be final and conclusive.

30.0 Arbitration

All disputes or differences in respect of which the decision is not final and conclusive shall, on the initiative of either party, be referred for adjudication as per the Arbitration And Conciliation Act 1996

31.0 Applicable law

The contract shall be interpreted in accordance with the laws of the union of India.

32. Notices

- 32.1 Any notice given by one party to the other pursuant to the contract shall be sent in writing or by telegram/ fax/ cable and confirmed in writing to the address specified for that purpose in the special conditions of contract.
- 32.2 A notice shall be effective when delivered or on the notice's effective date, which ever is later.

33. 0 Taxes and Duties

The contractor shall be entirely responsible for all taxes, duties, license fees etc. incurred until handing over of the contractor goods and services to the OMFED. All Government fees paid for inspections and approvals by statutory authorities shall be reimbursed by the OMFED on production of copy of treasury Challan for same. Service charges for depositing the govt. fees or submission of requisite forms with the statutory authorities shall be not being admissible.

33.0 Right of use defective equipment

If after handing over of the equipments and within the guarantee and warranty period, the operation or use of the equipment(s) proves to be unsatisfactory, the OMFED shall have the right to continue to operate or use such equipment

Until rectifications of defects errors or omissions by repair or partial or complete replacement is made, without interfering with the OMFED'S operation.

35.0 Jurisdiction

For the settlement of any dispute arising out of the contract against this bid, only the courts at Bhubaneswar only shall have jurisdiction.

SECTION-IV

SPECIAL CONDITIONS OF CONTRACT

ERECTION & COMMISSIONING OF EQUIPMENT

1.0 Sufficiency of Tender

The contractor by bidding shall be deemed to have satisfied himself as to all the conditions and circumstances affecting the contract price, as to the possibility of executing the works as shown and described in the contract, as to the general circumstances at the site of the works, as to the general labour position at site, and to have determined the prices accordingly.

2.0 Programme of installation and commissioning.

Within 30 days of receipt of letter of acceptance of the bid, the contractor shall submit to the OMFED for approval a comprehensive programme in the form of PERT Network / bar chart and any other form as may be required by the OMFED showing the sequence of order in which the contractor proposes to carry out the works including the design, manufacture, delivery to site, erection, hooking—up, commissioning, trial run & handover, thereof. After submission to and approval by the OMFED of such programme, the contractor shall adhere to the sequence of order and method stated therein. The submission to and approval by the OMFED of such programme shall not relive the contractor of any of his duties or responsibilities under the contract. The programme approved by the OMFED shall form the basis of evaluating the pace of all works to be performed by the contractor. The contractor shall update the PERT network every month, submit it to the OMFED and shall inform the OMFED the progress on all the activities falling on schedule for the next reporting date.

3.0 Preparations of drawings for approval

The contractor should visit the site to acquaint himself in respect of existing site conditions and to know the details/ information required for understanding the nature and type of civil construction works involved in the project.

The contractor shall submit to the OMFED for approval:

- a) Within the time given in the specification or in the programme, such drawings, samples, patterns and models as may be called for therein, and in numbers therein required.
- b) During the progress of works and within such reasonable times as the OMFED may required such drawings of the general arrangement and detailed of the works as the OMFED may require.

The specifications/conditions concerning the submission of drawings by the contractor are detailed as under:

Within four weeks from the date of receipt of the order, contractor shall furnish all necessary drawings, in three sets, (as briefly described below) for approval, identifying each drawing by a serial number and descriptive title. The list given below may be revised and extended if necessary, during the progress of work depending on the nature of the contract also.

The OMFED shall signify his approval or disapproval of all drawings or such drawings that would affect progress of the contract as per the agreed programmer.

Brief list of drawings:

- i) Equipment drawings for fabricated items.
- ii) Service piping layout in production and service blocks.
- iii) Electrical cable, conduit/cable tray layout.
- iv) Other miscellaneous drawings as required for erection work.

Drawings showing fabrication details, dimensions, layouts and bill of materials submitted for approval shall be signed by responsible representative of contractor and shall be to any one of the following sizes in accordance with Indian standards: AO, A1, A2, A3, and A4.

All drawings shall show the following particulars in the lower right hand corner in addition to contractor's name:

- i) Name of the OMFED
- ii) Project title
- iii) Title of drawing
- iv) Scale
- v) Date of drawing
- vi) Drawing number
- vii) Space for OMFED'S drawing number.

In addition to the information provided on drawings, each drawing shall carry a revision number, date of revision and brief description of revision carried out. Whenever any revision is carried out, correspondingly revision number must be up-dated.

All dimensions on drawings shall be in Metric Units.

Drawings (three sets) submitted by the contractor for approval will be checked, reviewed by the OMFED, and comments, if any, on the same will be conveyed to the contractor. It is the responsibility of the same contractor to incorporate correctly all the comments conveyed by the OMFED on the contractor's drawing. The drawings which are approved with comments are to be resubmitted to the OMFED for purpose of records. Such drawing will not be checked / reviewed by the OMFED to verify whether all the comments have been incorporated by the contractor. If the contractor is unable to incorporate any comments in the revised drawings, contractor shall clearly state in his forwarding letter such non-compliance along with the valid reasons.

Drawing prepared by the contractor and approved by the OMFED shall be considered as a part of the specification. However, the examination of the drawings by the OMFED shall not relieve the contractor of his responsibility for engineering design, workmanship, and quality of materials, warranty obligations and satisfactory performance of equipments, services & installation covered under the contract.

If at any time before completion of the work, changes are made necessitating revision of approved drawings the contractor shall make such revisions and proceed in the same routine as for the original approval.

4.0 Operation and maintenance manual:

The contractor shall furnish to the OMFED before the works are taken over, operating and maintenance instruction together with drawings of the works as completed, in sufficient detail to enable the OMFED to maintain, dismantle, reassemble and adjust all parts of the works, unless otherwise agreed, the works shall not be considered to be completed for the purposes of taking over until such instruction and drawing have been supplied to the OMFED.

5.0 <u>Contractor's superintendence and deployment of erection team and conduct of personnel</u>

The contractor shall employ one or more competent representatives, whose name or names shall have previously been communicated in writing to the OMFED by the contractor, to superintend the carrying out of the works on the site. The said representative or if more than one shall be employed, then one of such representatives shall be present on the site during all times, and any orders or instructions which the OMFED may give to the said representative of the contractor shall be deemed to have given to the contractor.

The said representative shall have full technical capacities and complete administrative and financial powers to expeditiously and efficiently execute the work under the contract.

The contractor shall, execute the works with due care and diligence within the time for completion and employ contractor's team comprising qualified and experienced engineers together with adequate skilled, semi-skilled and Unskilled workmen in the site for carrying out the works. The contractor shall ensure adequate work force to keep the required pace at all times as per the schedule of completion. The contractor shall also ensure availability of competent engineers during commissioning / start up, trial runs, operation of the plant / equipment till handing over of the plant.

The contractor shall furnish the details of qualifications and experience of their senior supervisors and engineers assigned to the work site, including their experience in supervising erection and commissioning of plant and equipment of comparable capacity.

When the contractor or his representative is not present on any part of the work where it may be desired to give directions in the event of emergencies, orders may be given by the OMFED and shall be received and observed by the supervisors or foremen who may have charge of the particular part of the work in reference to which orders are given. Any Such instructions, directions or notices given by the OMFED shall be deemed to have been given to the contractor.

The contractor shall furnish to the OMFED a fortnightly labour force report showing by classifications the number of employee engaged in work. The contractors' employment records shall include any reasonable information as may be required by the OMFED. The contractor should also display necessary information as may be required by statutory regulations, and shall comply with all statutory obligations as required under the prevailing rules of the state & country.

None of the contractor's supervisors, engineers, or labourers may be withdrawn from the work without notice to the OMFED and further no such withdrawals shall be made if in the opinion of the OMFED, it will adversely affect the required pace of progress and / or the successful completion of the work.

The OMFED shall be at liberty to object to any representative or person, skilled, semi-skilled or unskilled worker employed by the contractor in the execution of or otherwise about the works who shall in the opinion of the OMFED, misconduct himself or be incompetent, or negligent or unsuitable, and the contractor shall remove the person so objected to upon receipt of notice in writing from the OMFED and shall provided in that place a competent representative at contractor's own expense within a reasonable time.

In the execution of the works no persons other than the contractor, sub-contractor and their employees shall be allowed on the site except by written permission of OMFED.

6.0 OMFED'S Instructions

The OMFED may in his absolute discretion, issue from time to time drawings and/or instructions, directions and clarifications which are collectively referred to as OMFED's instructions in regard to:

Any additional drawing and clarifications to exhibit or illustrate details.

Variations or modifications of the design, quality or quantity of work or additions or omissions or substitution of any work.

Any discrepancy in the drawings or between the schedule of quantities and/or specifications.

Removal from the site of any material brought there by the Contractor, which are unacceptable to the OMFED and the substitution of any other material thereof. Removal and/or re-execution of any work erected by the Contractor, which are unacceptable to the OMFED.

Dismissal from the work of any persons employed there upon who shall in the opinion of the OMFED, misconduct himself, or be incompetent or negligent.

Opening up for inspection of any work covered up.

Amending and making good of any defects.

7.0 Rights of the OMFED

7.1 Rights to direct works:

The OMFED shall have the right to direct the manner in which all works under this contract shall be conducted, insofar as it may be necessary to secure the safe and proper progress and specified quality of the works. All work shall be done and all materials shall be furnished to the satisfaction and approval of the OMFED.

Whenever in the opinion of the OMFED, the Contractor has made marked departures from the schedule of completion or when circumstances or requirement force such a departure from the said schedule, the OMFED, in order to ensure compliance with the schedule, shall direct the order, pace and method of conducting the work, which shall be adhered to by the Contractor.

If in the judgment of the OMFED it becomes necessary at any time to accelerate the overall pace of the plant erection work, the Contractor, when directed by the OMFED, shall cease work at any particular point and transfer Contractor's men to such other point or points and execute such works, as may be directed by the OMFED and at the discretion of the OMFED.

7.2 Right to order modifications of methods and equipment

If at any time the Contractor's methods, materials or equipment appear to the OMFED to be unsafe, inefficient or inadequate for securing the safety of workmen or the public, the quality or work or the rate of progress required, the OMFED may direct the Contractor to ensure safety, and increase their efficiency and adequacy and the Contractor shall promptly comply with such directives. If at any time the Contractor's working force and equipment are inadequate in the opinion of the OMFED, for securing the necessary progress as stipulated, the Contractor shall if so directed, increase the working force and equipment to such an extent as to give reasonable assurance of compliance with the schedule of completion. The absence of such demands from the OMFED shall not relieve the Contractor of Contractor's obligations to secure the quality, the safe conducting of the work and the rate of progress required by the contract. The Contractor alone shall be and remain liable and responsible for the safety, efficiency and adequacy of Contractor's methods, materials, working force and equipment, irrespective of whether or not the Contractor makes any changes as a result of any order or orders received from the OMFED.

7.3 Right to inspect the work

The OMFED representative shall be given full assistance in the form of the necessary tools, instruments, equipment and qualified operations to facilitate inspection.

The OMFED reserves the right to call for the original test certificates for all the materials used in the erection work.

In the event the OMFED's inspection reveals poor quality of work/materials, the OMFED shall be at liberty to specify additional inspection procedures if required, to ascertain Contractor's compliance with the specifications of erection work.

Even though inspection is carried out by the OMFED or their representatives, such inspection shall not, however, relieve the Contractor of any or all responsibilities as per the contract, nor prejudice any claim, right or privilege which the OMFED may have because of the use of defective or unsatisfactory materials or bad workmanship.

8.0 Contractor's functions

The Contractor shall provide everything necessary for proper execution of the works, according to the drawings, schedule of quantities and specifications taken together whether the same may or may not be particularly shown or described therein, provided that the same can reasonably be inferred there from and if the Contractor finds any discrepancy therein, he shall immediately refer the same to the OMFED whose decision shall be final and binding on the Contractor.

The Contractor shall proceed with the work to be performed under this contract in the best and workman like manner by engaging qualified and efficient workers and finish the work in strict conformance with the drawings and specifications and any changes/modifications thereof made by the OMFED.

The work shall be carried out as approved by the OMFED or his authorized representative/s from time to time, keeping in view the overall schedule of completion of the project. The Contractor's job schedule must not disturb or interfere with OMFED's or the other Contractor's schedules of day-to-day work. The OMFED will provide all reasonable assistance for carrying out the jobs.

Night work will be permitted only with prior approval of the OMFED. The OMFED may also direct the Contractor to operate extra shifts over and above normal day shift to ensure completion of contract as per schedule. Adequate lighting wherever required should be provided by the Contractor at no extra cost. The Contractor should employ qualified electricians and wiremen for these facilities. In case of Contractor's failure to provide these facilities and personnel, the OMFED has the right to arrange such facilities and personnel and to change the cost thereof to the Contractor, on actual cost basis.

8.1 Third Party Insurance

Before commencing the execution of the works the Contractor, but without limiting his obligations and responsibilities, shall insure against his liability for any material or physical damage, loss or injury which may occur to any property, including that of the OMFED, or to any person, including any employee of the OMFED, or by arising out of the execution of works or in the carrying out of the Contract.

The Contractor shall, produce to the Engineer/OMFED the policy or policies of insurance and the receipts for payment of the current premiums, as and when required.

The terms shall include a provision whereby, in the event of any claim in respect of which the Contractor would be entitled to receive indemnity under the policy being brought or made against the OMFED, the insurer will indemnify the OMFED against such claims and any costs, charges and expenses in respect thereof.

Such insurance shall be for an amount not less than Rs.1, 00,000/- per occurrence, with the number of occurrences unlimited.

8.2 <u>Compensation for accidents or injury</u>

The OMFED shall not be liable for or in respect of any damages or compensation payable at law in respect or in consequence of any accident or injury to any workman or other person in the employment of the Contractor or any sub-Contractor, save and except an accident or injury resulting from any act or default of the OMFED, his agents, or servants. The Contractor shall indemnify and keep indemnified the OMFED against all such damages and compensation, save and except as aforesaid and against all claims, proceedings, costs, charges and expenses whatsoever in respect thereof or in relation thereto.

The Contractor shall insure against such liability with an insurer approved by the OMFED, which approval shall not be unreasonably withheld, and shall continue such insurance during the whole of the time that any persons are employed by him on the works shall, on demand, produce to the OMFED or OMFED's representative such policy of insurance and the receipt for payment of the current premium. Provided always that, in respect of any persons employed by any sub-Contractor, the Contractor's obligations to insure as aforesaid under this sub-clause shall be satisfied if the sub-Contractor shall have insured against the liability in respect of such persons in such manner that the OMFED is indemnified under the policy, but the Contractor shall require such sub-Contractor to produce the OMFED or OMFED's representative, on demand, such policy of insurance and the receipt for the payment of the current premium.

8.3 Duties of contractor Vis-à-vis other contractors:

Whenever proper execution of the work under the contract depends on the jobs carried out by some other Contractor, in such cases the Contractor should inspect all such erection and installation jobs and report to the OMFED regarding any defects or discrepancies. The Contractor's failure to do so shall constitute as acceptance of the other Contractor's installation/jobs as fit and proper for reception of Contractor's works.

The Contractor should also report any discrepancy between the executed work and the drawings.

The Contractor shall extend all necessary help/co-operation to other Contractor's working at the site in the interest of the work.

8.4 VARIATIONS

- 8.4.1 The OMFED shall make any variation of the form, quality or quantity of the Works or any part thereof that may, in his opinion, be necessary and for that purpose, or if for any other reason it shall, in his opinion be desirable, he shall have power to order the Contractor to do and the Contractor shall do any of the following:
- (a) Increase or decrease the quantity of any work included in the contract.
- (b) Omit any such work.
- (c) Change the character or quality or kind of any such work.
- (d) Change the levels, lines, position and dimensions of any part of the works, and
- (e) Execute additional work of any kind necessary for the completion of the works.

And no such variation shall in any way vitiate or invalidate the contract, but the value, if any, of all such variations shall be taken into account in ascertaining the amount of the Contract price.

8.4.2 No such variations shall be made by the Contractor without an order in writing of the OMFED. Provided that no order in writing shall be required for increase or decrease in the quantity of any work where such increase or decrease is not the result of an order given under this clause, but is the result of the quantities exceeding or being less than those stated in the Contract / Bill of Quantities. Provided also that if for any reason the OMFED shall consider it desirable to given any such order verbally, the Contractor shall

comply with such order and any confirmation in writing of such verbal order given by the OMFED, whether before or after the carrying out of the order, shall be deemed to be an order in writing within the meaning of this clause. Provided further that if the Contractor shall within seven days confirm in writing to the OMFED and such confirmation shall not be contradicted in writing by the OMFED within 14 days, it shall be deemed to be an order in writing by the OMFED.

- 8.4.3 All extra or additional work done or work omitted by order of the OMFED shall be valued at the rates and prices set out in the contract if in the opinion of the OMFED, the same shall be applicable. If the contract does not contain any rates or prices applicable to the extra or additional work, then suitable rates or prices shall be agreed upon between the OMFED shall fix such rates or prices as shall, in his opinion, be reasonable and proper.
- 8.4.4 Provided that if the nature or amount of any omission or addition relative to the nature or amount of the whole of the works or to any part thereof shall be such that, in the opinion of the OMFED, the rate or price contained in the contract for any item of the works is, by reason of such omission or addition, rendered unreasonable or inapplicable, then a suitable rate or price shall be agreed upon between the OMFED and the Contractor. In the event of disagreement of the OMFED shall fix such other rate or price as shall, in his opinion, be reasonable and proper having regard to the circumstances.

Provided also that no increase or decrease under sub-clause 8.4.1 of this clause or variation of rate or price under sub-clause 8.4.2 of this clause shall be made unless, as soon after the date of the order as is practicable and, in the case of extra or additional work, before the commencement of the work or as soon thereafter as is practicable, notice shall have been given in writing:

- a) By the Contractor to the OMFED of his intention to claim extra payment or a varied rate or price.
 Or
- b) By the OMFED to the Contractor of his intention to vary a rate or price.
- 8.4.5 If on certified completion of the whole of the works, it shall be found that a reduction or increase greater than 15 percent of the sum named in the Letter of Acceptance results from the aggregate effect of all Variation Orders but not from any other cause, the amount of the contract price shall be adjusted by such sum as may be agreed between the Contractor and the OMFED or failing agreement, fixed by the OMFED having regard to all material and relevant factors, including the Contractor's site and general overhead costs of the contract.
- 8.4.6 The Contractor shall send to the OMFED's representative once in every month an account given particulars, as full and detailed as possible, of all claims for any additional payment to which the Contractor may consider himself entitled and of all extra or additional work ordered by the OMFED which he has executed during the preceding month.

No final or interim claim for payment for any such work or expense will be considered which has not been included in such particulars. Provided always that the OMFED shall be entitled to authorize payment to be made for any such work or expense, notwithstanding the Contractor's failure to comply with this condition, if the Contractor has, at the earliest practicable opportunity, notified the OMFED in writing that he intends to make a claim for such work.

Note: This clause shall not be applicable for complete turn-key jobs.

8.5 Duties of the Contractor Vis-à-vis the OMFED

The equipment and the items, if any, to be supplied by the OMFED for erection, testing and commissioning by the Contractor, shall be as listed in the contract.

The Contractor shall keep a check on deliveries of all such equipment covered in the scope of erection, testing and commissioning work and shall advise the OMFED well in advance regarding possible hold-up in Contractor's work due to the likely delay in delivery of such equipment/components to enable him to take remedial actions.

8.6 <u>Preparation of foundation surfaces etc. for Erection of equipments:</u>

Contractor shall carry out final adjustments of foundations, leveling and dressing of foundation surfaces, bedding and grouting of anchor bolts, bed plates etc, required for seating of equipment in proper position. The Contractor seal be responsible for the reference lines and proper alignment of the equipment. However, all minor civil works which form and inseparable part of the installation and erection job like digging trenches for laying of cables, conduits and underground pipes, making cut-outs in walls, floors and ceilings for pipelines, adjustment, leveling, dressing and grouting of foundations, grouting of supports are to be carried out: by the Contractor at no extra cost. The necessary refilling/repairs of these cutouts, pockets and trenches shall be done by the Contractor: The Contractor should arrange for laying the supports, cut-outs, grouting of bolts, etc, when the civil works are in progress, so as to avoid refilling/repair works. The damages occurring to civil and other works are to be made good by the Contractor at Contractor's own costs.

9.0 Supply of tools, tackles and materials

The Contractor shall, at his own expense, provide all the necessary equipment, tools and tackles, haulage power, consumables, lubricants & sundries necessary for effective execution and completion of the works during erection, testing, commissioning & trial run.

10.0 Protection of plant

The OMFED shall not be responsible or held liable for any damage to person or property consequent upon the use, misuse or failure of any erection tools and equipment used by the Contractor or any his sub-Contractor's even though such tools and equipment may be furnished, rented or loaned to the Contractor or any of his sub-Contractors. The acceptance and / or use of any such tools and equipment by the Contractor or his sub-Contractor shall be construed to mean that the Contractor accepts all responsibility for

and agrees to indemnify and save the OMFED from any and all claims for said damages resulting from the said use, misuse or failure of such tools and equipments.

The Contractor or his sub-Contractor shall be responsible during the works, for protection of work, which has been completed by other contractors. Necessary care must be taken to see that the Contractor's men cause no damage to the same during the course of execution of the work.

All other works completed or in progress as well as machinery and equipment that are liable to be damaged by the Contractor's work shall be protected by the Contractor and protection shall remain and be maintained until its removal is directed by the OMFED.

The Contractor shall effectively protect from the effects of weather and from damages or defacement and shall cover appropriately, wherever required, all the works for their complete protection.

The contractor shall carry out the work without damage to any work and property adjacent to the area of Contractor's work to whomsoever it may belong and without interference with the operation of existing machines or equipment.

Adequate lighting, guarding and watching at end near all the storage, handling, fabrication, reassembly and erection sites for properly carrying out the work and for safety and security shall be provided by the Contractor at his cost. The Contractor should adequately light the work area during nighttime also. The Contractor should also engage adequate electricians/wiremen, helper etc. to carry out and maintain these lighting facilities. If the Contractor fails in this regard, the OMFED may provide lighting facilities as he may deem necessary and charge the cost thereof to the Contractor.

The Contractor shall take full responsibility for the care of the works or any section or portions thereof until the date stated in the taking over certificate issued in respect thereof and in case any damage or loss shall happen to any portion of the works not taken over as aforesaid, from any cause whatsoever, the same shall be made good by and at the sole cost of the Contractor and to the satisfaction of the OMFED. The Contractor shall also be liable for any loss of or damage to the works occasioned by the Contractor or his sub-Contractor in the course of any operations carried out by the Contractor or his sub-Contractors for the purpose of completing any outstanding work or complying with the Contractor's obligations.

11. Unloading, transportation and inspection

The Contractor shall be required to unload all the materials/equipment from the carriers. The Contractor shall plan in advance, based on the information received from the OMFED, Contractor's requirement of various tools, tackles, jacks, cranes, sleepers etc. required to unload the material/equipment promptly and efficiently. The Contractor shall ensure that adequate and all measures necessary to avoid any damage whatsoever to the equipment at the time of unloading are taken.

Any demurrage / detention charges incurred due to the delay in unloading the material/equipment and releasing the carriers shall be charged to the Contractor's account.

The Contractor shall be responsible for the reception and safe storage on site of all plant and equipment delivered or handled over to the Contractor, for the purposes of the contract.

The Contractor shall safely transport/shift the unloaded materials/equipment to the storage area and/or the place of work, as the case may be.

The materials/equipment would be carefully unpacked by the opening the wooden cases/other modes of packing as the case may be.

In case of equipments / materials to be supplied by the OMFED, all the materials / equipments received from OMFED prior to arrival of the Contractor at site, shall be handed over to the contractor who shall, thereupon, inspect the same & furnish the receipt to OMFED.

Detailed inventory of various items shall be prepared clearly listing the shortages, breakages / damages after checking the contents with respect to the Contractor's packing list, OMFED's order and approved drawings. The contractor shall also check every equipment for any shortage/shortcoming that may create difficulty at the time of installation, commissioning & trial run.

All the information and observations by the Contractor shall be furnished in the form of 'INSPECTION REPORT' to the OMFED with specific mention/suggestions which in the opinion of the Contractor should be given due consideration and immediate necessary actions, to enable the OMFED to arrange repair or replacement well in time and avoid delays due to non-availability of equipment and parts at the time of their actual need.

The protection, safety and security of the materials shall be the responsibility of the contractor, until they are handed over to the OMFED after erection, commissioning and testing and performance trial run as per the terms of the Contract.

12.0 Storage of equipment.

The Contractor shall be responsible for the proper storage and maintenance of all materials/equipment under the Contractor's custody. The Contractor shall take all required steps to carry out frequent inspection of equipment/materials stored as well as erected equipment until the same are taken over by the OMFED. The following procedure shall apply for the same:

The Contractor's inspector shall check stored and installed equipment/materials to observe signs of corrosion, damage to protective coating to parts, open ends in pipes, vessels and equipment, insulation resistance of electrical equipment etc. The Contractor shall immediately arrange a coat of protective painting whenever required. A record of

all observations made on equipment, defects noticed shall be promptly communicated to the OMFED and OMFED's advice taken regarding the repairs/rectifications. The Contractor shall there upon carry out such repairs/rectifications at his own cost. In case the Contractor is not competent to carry out such repairs/rectifications, the OMFED reserves the right to get this done by other competent agencies at the Contractor's responsibility and risk and the entire cost for the same shall be recovered from the Contractor's bills.

The Contractor's inspector shall also inspect and provide lubrication to the assembled equipment. The shafts of such equipment shall be periodically rotated to prevent rusting as well as to check freeness of the same.

The Inspector shall check for any signs of moisture or rusting in any equipment.

If the commissioning of equipment is delayed after installation of the equipment, the Contractor shall carry out all protective measures suggested by the OMFED during such period.

Adequate security measures shall be taken by the Contractor to prevent theft and loss of materials under the Contractors custody. The Contractor shall carry out periodical inventory checks of the materials stored and installed by the Contractor and any loss noticed shall be immediately reported to the OMFED. A proper record of these inventories shall be maintained by the Contractor. The Contractor should not sell, assign, and mortgages, hypothecate or remove equipment or materials, which has been installed or stored at the site under Contractor's custody without the written consent of the OMFED.

Suitable grease recommended for protection of surfaces against rusting (refined from petroleum oil with lancline minimum (70 DEG.CENT.) and water in traces) shall be applied over all equipment as required once in every three months. Quality of grease is to be approved by OMFED.

All equipment shall be stored inside a closed shed or in the open depending upon whether they are of indoor or outdoor design. Adequate storage area, as required, shall be made available by the contractor, within the site premises.

All the necessary items/goods required for protection as described above shall be arranged by the Contractor and such cost shall be included in the Contract price.

13.0 Approvals

The contractor shall obtain the necessary approvals of Factories & Boilers Inspectorate, Electrical Inspectorate, Legal Meteorology dept., Explosives Inspectorate and any other state/local authorities, as may be statutorily required or as may be directed by OMFED, and the cost of obtaining such approvals shall be included in the Contract price.

All the necessary details, drawings, submission of application and proformas will be furnished by the Contractor to the OMFED for verification/signature, and shall therefore be submitted to the appropriate authorities for approval.

The Contractor on behalf of OMFED shall submit the necessary application duly filled-in, together with the prescribed fees to the appropriate authorities. However, all the actual statutory fees paid by the Contractor shall be reimbursed by OMFED upon production of receipt. The contractor shall also make all necessary arrangements for inspection of the works by the statutory authorities, as and when required. Cost of all such inspections shall be included in the contract price.

Whenever necessary or required, the contractor shall furnish the necessary test and/or inspection certificates etc, from the appropriate authorities as per IBR, IER and other statutory regulations and the cost of obtaining these certificates shall be included in the contract price.

In case of capacity enhancement of existing plants, the contractor shall arrange for and obtain necessary approvals, as stated herein, for the entire expanded plant, either in phases or in whole as the case may be & the cost of obtaining such approvals shall be included in the Contract price.

Any modifications or changes required or advised by the appropriate authorities during the course of inspection and/or the contractor at his own cost shall carry out approval.

14.0 Review and co-ordination of erection work

The Contractor shall depute senior and competent personnel to attend the site coordination meetings that would generally be held at the site every month. The Contractor shall take necessary action to implement the decisions arrived at such meetings and shall also update the erection schedule, accordingly.

SECTION -IV (A)

SPECIAL CONDITIONS OF CONTRACT

(FOR MECHANICAL INSTALLATION)

MECHANICAL INSTALLATION

The installation work would comprise of:

- a) General installation i.e. positioning and installing all the equipments as per approved layout drawings and as per the contract.
- b) Supply and installation of structural platforms and tables.
- c) Supply and installation of all service piping including ancillary items.
- d) Insulation and cladding of piping equipment and electrical auto tracing of LSHS, including supply of materials.
- e) Interconnections of services and electrical with equipment.
- f) Guide line for expansion work.
- g) Clean up of work site.
- h) Supply of all cleaning chemicals and lubricants,
- i) Testing, commissioning and start-up.
- j) Painting including supply of paints as approved by the OMFED.
- k) Training of personnel.

Detailed specifications are given in the subsequent clauses.

2.0 GENERAL INSTALLATION

2.1 Positioning of equipment.

The work involves preparation of access for moving of the plant and equipment including their fittings from the work site godown or from the place within the site where they have been unloaded, to the place of erection, decrafting and placing on the foundation wherever required. All the civil foundations as per the manufacturer / Contractor's drawings shall be arranged by the bidder. The Contractor shall place the equipment and carry out final adjustment of the foundations including alignment and dressing of foundation surface, embedding and grouting of anchor bolts and bedplates. The Contractor shall be responsible for obtaining correct reference lines for purpose of fixing the alignment of various equipment. Tolerances shall be as specified in equipment manufacturers drawings or as stipulated by the OMFED's Engineer. No equipment shall be permanently bolted down to foundations or structure until the alignment has been checked by the Contractor and witnessed by the OMFED. The Contractor shall carry out minor alterations in the anchor bolts, pockets etc., at no extra cost and set the

equipment properly as per approved layout, drawings and manufacturer's instructions. The Contractor shall supply all the necessary foundation / anchor bolts and bedplates without extra cost.

The Contractor shall supply, fix and maintain, at his own cost, during the erection work, all the necessary centering, scaffolding, staging required not only for proper execution and protection of the said work but also for protection of the surrounding plant and equipment. The Contractor shall take out and remove any or all such centering, scaffolding, staging planking etc., as occasion shall require or when ordered to do so and shall fully reinstate and make good all things disturbed during execution of the work, to the satisfaction of the OMFED. The Contractor shall be paid no additional amount for the above.

3.0 CLEANING CONDITION AND LUBRICANTS

The necessary quantities of cleaning chemicals, lubricants, etc. required for the installation and commissioning, testing and start up of all the equipment till handing over are to be supplied the contractor and nothing extra would be paid for these.

4.0 TESTING, COMMISSIONING AND START UP

4.1 The contractor shall operate, maintain and give satisfactory trial run of the plant for a period of continuous 10 days (Ten Days) at the rated output, after satisfactory commissioning and start-up of the plant. All rectification of damages / defects and routine troubleshooting should be carried out by the contractor. The contractor shall incorporate / execute necessary minor modifications during the trial period for maximising operational efficiency. The contractor should also execute minor modifications as may be suggested by the manufacturer / OMFED. The contractor shall suggest recommended log sheet proformas for recording necessary operating data and pass it on to the OMFED in proof of satisfactory rated output and performance of the equipments / plant.

4.2 The commissioning shall also include the following for each equipment:

- 4.2.1 Field dis-assembly and assembly.
- 4.2.2 Clean out of lubrication system including chemical cleaning wherever required.
- 4.2.3 Circulation of lubricant to check flow.
- 4.2.4 Clean out and check out of all the service lines.
- 4.2.5 Check out and commissioning of instruments, equipment and plants, filtering of transformer and other oils so that if deteriorated, they shall attain the required properties/standards, specified tests in this regard must be carried out by approved authorities and their satisfactory reports submitted to the OMFED before start-up.
- 4.2.6 Recharging or make-up filling of lubricant oil up to the desired level in the lubrication system of individual machine.

- 4.2.7 Operation in empty condition to check general operation details wherever required and wherever possible.
- 4.2.8 Closed loop dynamic testing with water wherever required.
- 4.2.9 Operation under load and gradual load increase to attain maximum rated output.
- 4.2.10 Trouble shooting during the trial period.
- 4.3 The Contractor shall demonstrate proper working of all mechanical and electrical controls; safety and protective device, in presence of the OMFED's engineer and the same should be duly recorded.
- 4.4 After conducting testing, in case a particular equipment is not working properly or not giving rated output the Contractor will furnish a detailed report to the OMFED stating therein the detailed account on the performance of the equipment with possible reasons for improper or not working of the same in case such equipment is supplied by OMFED.

The OMFED after receipt of report from the Contractor would take up the matter with the manufacturers and if required would invite the representative of original manufacturers. In case the OMFED considers that the nonperformance of equipment is only due to in-experience of the Contractor, then the charges incurred for the manufacturer's representative visit would be debited to the Contractor's account.

- In case of turnkey contracts, the contractor shall furnish a detailed account of the performance of all the equipments. In case any particular equipment fails to perform properly or at its rated output, then the contractor shall take up the matter with the original manufacturer, under intimation to OMFED. In case OMFED considers it necessary, the contractor shall invite, at his own cost, the technical personnel of the original manufacturer to visit the site & carry out necessary rectification/modifications to get the rated performance. In case the contractor fails to do so within 7 days of receipt of instructions from OMFED, the OMFED shall take necessary action to invite the representatives of the Original manufacturer to visit the site & the cost of such visit(s) shall be debited to the contractor's account.
- 4.6 Further before commencement of testing of commissioning, the OMFED reserves the right to invite the original manufacturer's representative at the cost of the Contractor for start-up help, assist and guide the Contractor during commissioning in the following cases:
 - a) The Contractor has no previous experience of commissioning and start-up of the similar equipment.
 - b) The OMFED is of the opinion that the Contractor is not capable to commission and start-up of certain specific equipment.

However, in either of the cases the manufacturer's representatives would be called with prior information to the Contractor and the Contractor will have to

extend all co-operation to such representatives in good spirit and in the interest of the work.

4.7 After satisfactory commissioning and start-up the Contractor shall keep his representatives under whose supervision the OMFED's staff shall be operating and maintaining the plant and equipment for the trial run period of 30 days. The Contractor's representatives should be present at all times during the running and operation of plant and equipment. During this period the Contractor shall ensure proper working of complete plant and equipment and attend any works required to be done and shall also take complete responsibility for proper operation and maintenance of the complete plant and equipment.

5.0 PAINTING

All the equipment/machineries like motors, pumps, HT / LT panel, transformer, switch boards, starters, junction boxes, isolators, storage tanks, supporting structures, pipe supports and MS / GI pipes and all exposed and visible iron parts included in the scope off erection / commissioning shall be given double coat of paint of approved shade over a double coat of anti-corrosive primer wherever necessary.

Irrespective of the condition of original paint of equipment / machineries / structures / supports. All surfaces wherever required must be properly cleaned from scale, dirt and grease prior to painting. Spray painting must preferably be used on all the equipment / machineries and wherever practicable. Suitable and necessary cleaning / wiping of sight / dial glasses, other non-metallic parts, flooring, walls and other surfaces which have been spoiled by paint during painting must also be carried out by the Contractor.

Lettering and other markings, including capacity and flow direction markings, shall also be carried out by the Contractor on the tanks, pipe lines, starter's, motors, isolators and wherever else necessary, as directed and as per the standard practice of installation. ISI colour codes and colour charts as mentioned in Annexure-III must be adhered to. Supply of all paints and all other materials required it included in the scope of supply of the Contractor under this contract/order.

6.0 TRAINING OF PERSONNEL

Necessary staff as may be deputed by the OMFED shall be trained by the Contractor for operating the plant. The personnel will be associated for the training during the installation, testing, commissioning, start-up and trial run period and the training tenure shall be extended for a minimum period of one month from the date of commissioning and start-up.

SECTION -IV (B) SPECIAL CONDITIONS OF CONTACT FOR ELECTRICAL INSTALLATION

1.0 SCOPE

The intent of this specification is to define the requirements for the installation, testing and commissioning of the electrical system like high tension switch yard with accessories and equipments, transformers, HT panels, oil circuit breakers, LT panels and power control centers, Distribution boards, capacitors and banks panels, power and control cables, remote push button stations, motors, earthing network, etc. Requirement of a particular project shall be as specified in schedule of quantities.

2.0 STANDARDS

- 2.1 The work shall be carried out in the best workman like manner in conformity with this specification, the relevant specification / codes of practice of the Indian Standards Institution, approved drawings and the instructions issued by the Engineer-in-charge or his authorised representatives, from time to time. Some of the relevant Indian Standards are listed in Annexure-IV.
- 2.2 In addition to the standards as mentioned in 2.1, all works shall also confirm to the requirements of the following:
 - a) Indian electricity act and rules framed there under.
 - b) Fire Insurance Regulations.
 - c) Regulations laid down by the chief electrical inspector of the state / Electricity board.
 - d) Regulations laid down by the factory Inspector of the state.
 - e) Any other regulations laid down by the local authorities.
 - f) Installation & operating manuals of original manufacturers of equipments.

3.0 **EQUIPMENT AND ACCESSORIES - SPECIFICATIONS**

This defines specifications and requirements mainly for the equipment and accessories which are generally supplied by the erection agencies and do not cover the specification of main electrical equipment such as Transformers, HT. and LT. panels, switchboards and motors etc. which may be supplied by the OMFED.

All materials, fittings and appliances to be supplied by the contractor shall be of best quality and shall confirm to the specification given here under. The equipment shall be manufactured in accordance with current Indian Standard Specifications wherever they exist or with the BS or NMA specifications, if no such ISS are available. In the absence of any specification, the materials shall be as approved by the OMFED or his authorized representatives.

Makes of bought out items selected by the Contractor must be furnished by him as per the Performa given in Annexure-V.

3.1 **Control Cables**

Control cables for use on 415 V system shall be of 1100 volts grade, copper conductor, PVC insulated, PVC sheathed, armored and overall PVC sheathed, strictly as per IS: 1554 (Part I) - 1976. Unarmored cable to be used only if specifically mentioned in schedule of quantities.

The size of these cables shall be as specified in schedule of quantities or as per erection drawing. THE MINIMUM CONDUCTOR DIAMETER SHALL BE 2.5 SQMM.

3.2 Motor Isolators

These shall be in Aluminum cast housing, completely dust, vermin and weather proof, suitable for 25A, 415 volts, 50 Hz with rotary type switch and reroll type metallic plug, complete with cable gland for incoming and outgoing cables. Operating hand to be of metal and final finish of housing to be buffer mirror. Sample to be got approved before supply.

SECTION - V

TECHNICAL SPECIFICATION

1. Online Pasteuriser – 5KLPH

CAPACITY – 5KLPH (SKID MOUNTED)

Make: IDMC / Tetrapak/ GEA

TEMPERATURE: Programme 5-45-65-80-4 ° C.

REGENERATION - 90%

HOLDING TIME - 20 secs in Tubes.

SCOPE OF SUPPLY:

PLATE HEAT EXCHANGER: PHE should be SS 316 with gasket of NBR food grade material which would be consist of fix plate and four intermediate plates. The frame of the PHE should be cladded in SS304 and should be provided with SS ball feet. This PHE will be connected with cream separator after reaching 45-48 degree C. It will also be connected with Homogenizer when milk temperature is 63 to 67 degree C. Flow diversion valve to be provided in the system.

FLOAT BALANCE TANK: - 100 ltrs capacity fabricated from 2 mm thick AISI 304 stainless steel sheet with cover, float, outlet and adjustable stainless steel ball feet.

<u>AUTOMATIC FLOW CONTROLLER</u>: (stainless steel) to maintain the required flow rate irrespective of the pressure loss.

S. S DUPLEX FILTER with suitable pore size to continuously filter the product. The design should be such so as to facilitate quick dismantling of the filter element complete with changeover valves at inlet and outlet and air purging arrangement.

STAINLESS STEEL MILK PUMP (7.5HP) to match with the pasteurizer capacity. The TEFC drive motor should be fitted with SS shroud with louvers for air cooling and suitable arrangement for cabling.

Stainless steel hot water set consisting of mixing chamber auto steam flow regulating valve, pressure relief valve, overflow discharge, hot water circulating pump (Cap-15, 000 LPH) with all inter connecting SS pipes & fittings. The hot water pump should be fitted with SS shroud with louvers for air cooling & suitable cabling arrangement.

Automatic control panel shall consist the following:

The panel should be of floor mounted design dust, weather and vermin proof fabricated from 2 mm thick SS sheets of AISI SS 304 material. It should be lockable type.

- 1. One no two pen temp. recorder with serving element for recording hot and chilled milk temperature. The recorder will be of circular/ chart type having a range 0 degree, -120 ° C with a straight drive suitable for operation on single phase 230 V, 50 C/s AC supply.
- 2. One no digital temp. indicator mounted on the panel to indicate the hot milk temp. Continuously. This shall be sensed through a PT -100 sensor. PI indicating controller, EPT, Steam flow regulating valve, PT-100 sensor senses the hot milk temp. and gives a signal to PID controller which in turn actuates EPC to give the required air signal to steam flow regulating valve. Thus the flow of steam into the hot water tank is controlled in proportion to

hot milk temp. so that the pasteurization or hot milk temp. is maintained at the present value (Temp. accuracy +0.5 ° C)

- 3. Pasteurizer shall also be provided with an **AUTO FLOW DIVERSION VALVE**. This valve is actuated whenever the pasteurization temp goes below the present value, thereby enabling milk to divert back to FBT. There shall be an audiovisual alarm provided for this purpose.
- 4. An air filter cum pressure regulator shall be provided to control and supply air to instruments at the present value along with a pressure gauge to indicate the pressure.
- 5. The control panel should also have a minic diagram showing the flow of milk & service media at various stages of the pasteurizer.
- Set of push buttons, rotary switch indicating lamps should be provided on the panel and prewired to indicate automatic diversion/ forward portions of **FDV** as the situations may be. ON and OFF push button with indicating lamps with suitable inscriptions shall be provided for the following pumps:

Hot water Pump - 1 No.

Chilled water pump - 1 No.

Emulsifying Pump - 1 No.

One no. main alternator with key and indication lamp for On - Off.

7. Heat Exchange Model PAP -5:

Plates - The plates shall be made from SS confirming to AISI 304 and of sanitary design. This should be readily removable for cleaning & inspection.

Gaskets:

The sealing gasket shall ensure complete sealing & prevent cross leakage between product and service liquid. The gasket materials shall be NBR food grade Nitrile rubber and withstand the pasteurization temperature & CIP cleaning solutions.

Holding sections:

It shall be designed to hold the product for minimum specified holding time at the pasteurization temperature.

Supporting Frame:

The supporting frame for the plate pack shall be of a self-supporting design made from SS (AISI 304) with necessary tightening arrangement. The frame shall have adjustable ball feet.

Inlets / Outlets:

The inlet and outlets in each sections of the heat exchanger for products and services shall be provided with complete SS (AISI -304) unions. Stainless cavity for thermometers on all the inlets and outlets of products and steel (AISI -304) products services complete with a SS guard of at least 200mm length for mounting glass thermometers five nos. Glass thermometers shall be provided to measure inlet outlet or milk, pasteurized milk outlet inlet and outlet of heating and cooling media.

The heat exchanger shall have inlet & outlet connections for connecting milk clarifier at 45 ° C and homogenizer at 65° C. Hence there shall be total 5 sections with necessary dividing plates.

There shall be total 201 nos. of plates having heat transfer areas of 0.40 sqm per plate with a total heat transfer area of 80.4 sqm.

Safety Device.

A safety device shall be provided in the hot water side of heating sections to avoid damage to the heat exchanger caused by excessive pressure. It shall be of sanitary design.

- **8**. One set of suitable size inter-connecting SS pipes and fittings to connect the FDV, Feed Pump, Heat Exchanger duplex filter, FDV to FBT forward diverted line etc. with necessary SS pipe supports & SS clamps.
- **9.** a) Two sets of manual along with relevant drawings including control diagram.
 - b) A set of standard tools shall be supplied with the equipment.

10. <u>Flow diversion valve</u>: Whenever the temperature of the Pasteuriser goes down then standard fixed the forward flow to the Silos will stop and milk will be diverted to Pasteuriser balance tank.

11. ERECTION & COMMISSIONING:

SCOPE OF SUPPLY:

Unpacking of the equipment shifting of the equipment to the desired place. Positioning of the equipment in its place. Inter-connection of the equipment with SS & service pipelines.

The erection of the above shall be carried out by you which would also include the followings:

- a) Steam diaphram valve.
- b) Pipeline connection to inlet of Hot water mixing battery after steam diaphram.
- c) Inter-connecting SS piping between FBT, pump, Duplex filter FDV & pasteurizer.
- d) Hot water piping between hot water set and pasteurizer and back.
- e) Airline from control panel, FDV, Diaphram valves.
- f) Control cables from panel board to pasteurizer PT -100.
- g) Flow diversion valve etc. pipeline from FDV to FBT.

After installation of equipment, the pasteurizer set shall be put on trial run for a period of 3 days to see the performance, capacity measurement etc.

Drawings:

You shall send us 03 sets of general arrangement & fabrication drawings of all items, diagram of the pasteurizer showing the pass & flow arrangement of milk & service media, drawing for inter connecting pipes and fittings with pipe supports, electric / pneumatic control diagram etc. within 15 days of receipt of the purchase order for our approval. We shall send you the approved drawings within seven days of receipt provided the drawings are in order.

Guarantee:

The equipment shall be guaranteed for a period of 12 months from the date of commissioning and 18 months from the date of supply.

2. Online Milk Homogeniser – 5KLPH (<u>skid mounted</u>)

Functional Requirement:

5,000LPH capacity Homogenizer at 200 kg./cm² shall be suitable for breaking & dispensing milk fat globules having 4.5% fat & 8.5% SNF to less than 2-3 microns and shall work at more than 90% efficiency.

Make - IDMC, APV, GEA / Bartolli.

Capacity – *5,000LPH*

Max. working pressure –200 Kg./Cm², Two stage design with first stage 2500 PSI and second stage 500 PSI

Electric Power - The motor should be designed accordingly,

No. of Plungers – 3,

Material of plunger – S.S.316 chrome plated.

Homogenizing Head – two stage hydraulic actuated with stellated valve & valve seat. Impo,

stellite mall rich.

Homogenized valves – Satellite Grade – 20 materials.

CRANK CASE:

- i) Rugged in construction and easily openable.
- ii) Open type split crank case body for easy checking and maintenance.

HOMOGENISING HEAD

Homogenising Head shall be two stage, removable type, hydraulically operated with in-built Relief Valve for excess pressure.

Homogenising Valve and valve seats for both 1^{st} and 2^{nd} stage are of Satellite Grade – 20 materials. They are wear and abrasion resistant and of interchangeable and replaceable type.

PLUNGERS

Plungers are made out of Hardened Special Alloy steel in order to ensure good life for plunger packing.

PLUNGERS PACKING

Plunger packing with sealing lip to prevent leakage and easily replaceable.

Cooling is to be done preferably by water.

The plunger seal are of Food Grade quality, able to withstand 90° C temperature.

LUBRICATION:

- i) Forced feed lubrication through gear pump mounted on the shaft.
- ii) Low & high pressure cut off switches for lubrication system.
- iii) Oil level safety switches.

COOLING:

- i) Crank case oil cooling through tube type oil cooler to ensure that the temp. of oil does not rise above 55°C.
- ii) Gear Box cooling through water jacketed in-built in gear box casing.

POWER TRANSMISSION:

The primary transmission of power in Homogeniser shall be through 'V' belt and pulleys. The device with all the pulleys and 'v' belt etc. shall be on the main frame inside the shroud only. Both the pulleys (i.e. Motor as well as Homogeniser) shall be provided with Luck bush arrangement. The secondary power transmission shall be through a shaft mounted gear box located within the S.S shroud.

FINISH:

All welding joints grounded smoothly. All S.S. surfaces would be polished to 150grit.

JOINT CURVATURE:

There will not be any sharp corner edges on milk contact surfaces.

Also there would not be any thread in contact with the product.

SUITABILITY:

The Homogenizer would be suitable for use on reconstituted skimmed milk mixed with fat in the form on molten butter oil at a temp. of 55 to 65°C. The fat content of the mix would not exceed 12%.

CLEANING:

The Homogenizer should be suitable for CIP cleaning line in line with the pasteurizer.

PAINTING:

The body of the homogenizer to be painted with coat of epoxy primer followed by two coats of epoxy paint after thorough de-rusting.

TOOLS:

1 set of essential tools for commissioning and maintenance of the Machine should be supplied along with the Machine.

MOTOR CONTROL CENTRE

Motor control centre made from CRCA sheet powder coated shall be supplied with STARTER suitable as per the rated capacity given in the technical specification and DOL STARTER for the Hydraulic pump shall be provided. The panel shall be dust and vermin proof.

N.B:

All milk contact surfaces to be made of S.S. confirming to AISI 316. The complete unit would be provided with removable S.S. enclosures to give sanitary outlook.

ACCESSORIES:

- The inlet/outlet for product will be made up of 63.5 mm size with SMS connection.
- Pressure gauge of imported flat diaphragm type, glycerine filled, sanitary design as per standard 1 No.
- Instruction Manual 03 No.

- Electrical Control panel with starters & on off switches should be supplied. The panel would be out of M.S. Powder coated.

Note: The bidder shall send their Engineer for installation and commissioning of the homogenizer at site free of cost. The efficiency of the homogenizer shall be shown to us for consecutive runs for more than 90% homogenizing efficiency.

3. Online Cream separator – 5KLPH

Make: HMT / IDMC / Tetrapak / GEA

Rated Capacity : 5000 Ltrs/hr

Bowl : Solid wall bowl

Product Discharge : Closed discharge with double centripetal pump

Cleaning : Manual cleaning after dismantling of the bowl

Frame : Cast iron, varnished in RAL 7037, grey

Drive system : Flat belt drive with centrifugal clutch

Maximum feed pressure : 1.0 bar

Useful discharge pressure : 4.0 bar

(Skimmed Milk)

Useful discharge pressure cream: 4.0 bar

Product feed temperature : 45 - 55 Deg C

Cream Fat percentage : Not less than 60%

Dimensions : L 815 mm x W 470 mm x H 1035 mm

Bowl weight : 50 kgTotal weight : 305 kgMotor power : 7.5 kW

Starting type : Star/delta

Documentation : 1 set of documentation in English

Accessories:

- 1 foundation frame to be integrated in the floor structure
- 1 set of tools for dismantling, lifting and assembling of the bowl
- 1 set of spare parts for commissioning
- 1 set of manual valves and indicating instruments for the adjustment of skim milk discharge pressure and cream flow

4. Milk Can Washer - 600 Cans/hr.

(STRAIGHT THROUGH CAN WASHER)

CAPACITY: 600 Cans/hr.

FUNCTIONAL REQUIREMENTS:

It would be used for drip draining, washing, sterilising and drying standard milk cans and can lids.

DESIGN REQUIREMENTS

Capacity: 600 Cans/hr.

Configuration: Straight through

Washing Sequence

Fresh water pre-rinse

Pressure hot water first rinse having minimum 3.5 Kg/sq.cm discharge head and 55 Deg. Celsius temp. (return water from after rinse should be used).

Pressure hot detergent cleaning having minimum 3.5 Kg/sq.cm discharge head and 70 Deg. Celsius temp.

Pressure hot water after rinse having minimum 3.5 Kg/sq.cm discharge head and 80 Deg. Celsius temp.

Live steam sterilisation.

Hot air drying at 100 Deg. Celsius temp.

Available Services:

Steam: at 3.4 Kg/sq.cm pressure

Water: Well water at 3 Kg/sq.cm

<u>Finish</u>: All welding joints are to be ground flush and finished to 150 grit. All stainless surfaces are to be polished 150 grits.

SCOPE OF SUPPLY

<u>Main Enclosure</u>: The main enclosure which houses the washing sterilising and drying sections should be made from 2mm thick stainless steel sheet conforming to AISI 430 having removable stainless steel (AISI 4001 inspection doors all along its length at front side for easy access. Can guides should be provided all along the inside length.

3.2 <u>Under Frame</u>: The complete underframe should be made from mild steel. The complete assembly should have sufficient number of solid steel legs with stainless steel ball feet having 50mm vertical adjustment. The complete mild steel frame should be spray galvanised after fabrication and proper surface preparation.

<u>Conveyor Chain</u>: The machine conveyer must ensure that, the individual cans and lids remain properly spaced. The drive motor, transmission, drive shaft and idler shaft should have adequate and accessible provision for adjustment and tensioning.

Drip Saver:

It should be fabricated from 2 mm thick stainless steel sheet confirming to AISI 304. It should be 5500mm long and supplied as an integral part of the machine where drips from emptied cans / lids enter washing section. A suitable stainless steel outlet with stainless steel drain cock should be provided in the drip saver away from the can washer body. It should be given a generous slope towards the outlet for free flow of milk.

- 1 no.

Condensate Box: The vapour duct ending in a condensate box should be provided on top of the can washer for condensing flash vapour from the can washer. The warm waters from the condensate box can be used in the hot water section of the can washer. The condenser and duct should be made from stainless steel conforming to AISI 430. There should also be an exhaust blower of suitable capacity mounted on flanged type motor to suck vapour from the can washer and throw out condensable gases. Exhaust fan should have protection against chemical fumes and moisture. The exhaust fan impeller should be of SS casting. -1 no.

<u>Can Discharge</u>: The clean and dry cans should be discharged from the machine on to a clean can conveyor. The system should also be provided with a mechanical arrangement to place the clean lids manually on the cleaned cans.

Washing Stations:

<u>Washing</u>: The pumping and jetting arrangements should apply sufficient washing liquid to the inside an outside surfaces of the cans and the lids.

<u>Filters</u>: In recirculation of liquid in first rinse, detergent section and after rinse plate type suction filters should be provided to prevent choking of pump impeller and nozzles. The filter should be fabricated from AISI 430 SS material -3 set

<u>Sump tanks</u>: These should be made from stainless steel AISI 430 and would be used as feed tanks for various washing liquids. Correct operating levels should be maintained automatic in all the sump tank by necessary float valves. There should not be any intermixing between the different liquids. -3 nos.

<u>Water Heating Arrangement</u>: For hot water direct steam injection system should be provided with steam water ejector for mixing steam with water. For detergent heating indirect system with SS heating coil ending in a steam trap should be provided. Condensate from the coil should be discharged into the hot water tank. Suitable drain points to be provided to drain the used liquid.

<u>Air Heating Arrangement</u>: For can drying hot air to be used and blower, air heater and ducting etc. should be provided. Impeller housing of blower and ducting should be from SS 430 whereas coal of air heater from copper tubes of 14 G.

Jet Nozzles: Nozzles for jets should be made from stainless steel conforming to AISI 316. - 1 lot

No Can No Jet: No can no jet system should be provided for pre-rinse water and steam sterilisation sections.

<u>Dosing Device</u>: Manual gravity operated dosing device fabricated from SS 304 to maintain strength of detergent.

<u>Pumps</u>: The centrifugal monoblock type pump set having cast iron impeller, cast iron body and SS sheet with mechanical seal having 35 MWC discharge pressure should be supplied having capacity 20000 1ph should be supplied. -3 nos.

<u>Instruments</u>: Suitable connections/Thermowell should be provided on the delivery sides of the pumps and on the sump tanks for fixing pressure and temperature gauges

Control Panel: 1 no.

<u>Main Enclosure:</u> The enclosure and supporting structure should be made from stainless steel conforming to AISI 430. The enclosure should be moisture, dust and vermin proof.

<u>Minic Diagram</u>: It should show the complete can washing Process including can conveying system with LEDs showing the operation of various motors.

<u>Push Buttons and Indicating Lamps</u>: ON/OFF push buttons for all the motors and six sets as extra. All the push buttons should have indicating lamps and buttons suitable inscriptions.

- 3.9.4 <u>Wiring</u>: The control panel should be completely prewired. The wiring should be done by copper wires in accordance with the standard practice.
- 3.10 <u>Termination Points</u>: All distribution piping should be preassembled and terminated at a single flange for each service connection. Suitable weather proof electrical terminal box with power terminal blocks should be provided. All power wiring through isolators and earthing for various motors from this terminal box should be done with copper conductor multi-core cable in suitable 'A' class GI pipes. Erector would provide only power from Motor Control Centre to this terminal box for all motors.

Painting: The spray galvanised under frame should be painted with two coats of epoxy primer.

4.0 REMARK

4.1 Type (L/H or R/H): Facing the front side (side having inspection doors) of can washer, if the can conveyor moves from right to left then the can washer would be called as called left hand type and the reverse as right hand type.

5. Milk Silo - 10 KL

Type : VMST type

Material : a) Inner shell - AISI 304 (3 mm thick)

b) Outer cladding - AISI 304 (2 mm thick)

Finish : 2B with the joints ground & polish to 150 Grit. Pre-coated sheet shall be used

for silo construction

Agitation : Single mechanical agitator to ensure uniform fat distribution without any

adverse effect on the contents.

Ports and fittings : Inlet/outlet, breather, CIP spray ball, high and low-level sensors (only provision), level transmitter (only provision), temperature sensor, man way, alcove and other standard

accessories like light glass, sight glass

Insulation: PUF/THERMOCOLE Insulation of suitable thickness to ensure temp. rise does not

exceed 1 Deg. C in 24hours time.

Instruments : RTD and digital temperature indicator to be provided

Volume marking: Silo inner cell should be marked for volume.

6. Two Stage PHE – 1KLPH

PHE should be SS 316 with gasket of NBR food grade material which would be consist of fix plate and four intermediate plates. The frame of the PHE should be cladded in SS304 and should be provided with SS ball feet.

7. Multi Purpose Vat - 1 KL

FUNCTIONAL REQUIREMENTS

Multipurpose vat would be used for heating of milk from 4° C to 85° C and coagulating the same at 85° C for production of paneer & chhana indirectly with live steam at atmospheric pressure in the jacket and cooling at 37° c by well water.

DESIGN REQUIREMENTS

Capacity: 1000 L

Constructional Features: The vat should be tripled wall welded construction, jacketed and insulated having rectangular cross section.

Dimensions of Vat:

Inner Vat	Inner vat length	Inner vat width	Inner vat depth at outlet side	Inner vat depth at opposite side
1000 L	2000 mm	1250 mm	520 mm	500 mm
Jacket	Jacketed vat length	Jacketed vat width	Jacket depth at outlet side bottom	Jacket depth at opposite bottom
1000 L	2100 mm	1350 mm	50 mm	50 mm
Outer vat	Outer vat length	Outer vat depth	Outer depth at outlet side	Outer vat depth at opposite side
1000 L	2200 mm	1450 mm	620 mm	620 mm

Slope: Both the inner and outer shells should slope towards the whey outlet as per the dimensions given above for free and complete drainage of the liquid.

Finish: All welding joints are to be ground smooth. All stainless steel surfaces are to be polished to 150 grits.

Joint Curvatures: All inside corners should have minimum radii of 25 mm

SCOPE OF SUPPLY

Inner Vat: The inner vat should be made from minimum 3 mm thick stainless steel sheet conforming to AISI 304.

Jacket: Steam jacket of minimum 50 mm width at all the four sides and the bottom should be provided. The jacket should be well supported with SS spacer pipe pieces.

Insulation: 50 mm thick mineral glass wool insulation should be provided after coating inner side of the outer vat and outer side of the jacket by bitumen paint. The insulation material shal be tightly wrapped on the jacket before fixing outer vat.

Outer vat: The outer vat should be made from minimum 2 mm thick stainless steel sheet conforming to AISI 304.

Accessories:

Steam Distribution: Steam distribution system should comprise one no. of sparger pipe for 500 L and two Nos. for higher capacity, provided at the bottom jacket. The steam sparger should terminated outside with flange. The flange shall be provided with a steam orifice plate and 25 NB steam valve. 1 set

Over Flow: SS 304 overflow pipe of 38 mm diameter for the jacket ending near the floor level. 1 No.

Condensate drain: At the bottom of the jacket, suitable condensate outlet with valve & steam trap assembly shall be provided.

Safety Valve: In the jacket a safety valve should be provided to avoid any pressure accumulation in the jacket. The jacket shall normally work under ambient pressure.

Chilled Water connection: For cooling application, near to the steam sparger side a chiller water connection of 25 NB compete with valve shall be provided in the jacket.

Whey Outlet: Stainless steel cup type outlet of diameter 51 mm with stainless steel flanged vale (one end flanged other end SMS union) for the vat. Outlet should be at a height of 230 mm from the finished floor level.

1 No.

Drain: Suitable stainless steel 25 mm dia drain with valve for the jacket. This drain connection shall be used for drainage of cooling water from the jacket. 1 No.

Strainer: Sliding type strainer for the whey outlet (item 3.5.6). The strainer should be made from SS 316 wire mesh fixed in frame. 1 No.

Legs: Mild steel legs 38 mm dia with stainless steel (AISI 304) pipe cladding with stainless steel ball feet provided at the bottom of the tank. The ball feet should have provision for height adjustment of 50 mm, 4 Nos. for cap upto 1000 L and 6 Nos. above it.

<u>MANUFACTURING CODE</u>: The multi purpose vat shall be manufactured following good engineering manufacturing practices.

<u>INSPECTION & TESTING</u>: OMFED reserve the right to inspect the equipment during various stages of fabrication. The following tests should be conducted by the manufacturers at their works. Dye penetration test for all stainless steel welding joints.

Water fill-up test of inner vessel for water tightness and hyd. test at 2.5 kg/cm² for jacket.

<u>DRAWING</u>: Bidder shall submit a GA drawing of the equipment along with the offer giving details of the material of construction, details of the bought out items etc. However, successful bidder has to submit detailed manufacturing drawings for approval from OMFED, prior to start fabrication.

<u>INTALLATION & COMMISSIONING</u>: Installation, testing & commissioning of the multipurpose vat is in the scope of the bidder. Detail scope & general guidelines for installation is given in the separate annexure.

8. Khoa/Rabidi Pan - 240 Ltr

(STATIONARY/TILTING TYPE)

Volume of the dish 240 Ltrs. triple walled with inner of 6 mm thick SS 304 material & intermediate shell of 5 mm thick MS material insulated with 100 mm thick mineral wool and covered with 2 mm thick SS sheet. The Khoa Pan should be specially designed dish, having greater surface area for effective evaporation. The above Khoa Pan shall be fitted with the following accessories and mounting: -

01. Temperature Gauge	0-150 deg. C.	- 1 No.
02. Pressure Gauge	0-50 PSI	- 1 No.
03. Release Valve	1/2"	- 1 No.
04. Safety Valve	3/4"	- 1 No.
05. Steam Trap	1/2"	- 1 No.
06.C.I. Strainer	1/2"	- 1 No.
07.S.S. Stirrer		- 2 Nos.
08. Steam Inlet Valve	1/2"	- 1 No.
09. Thermostatic Airvent	1/2"	- 1 No.
10. Air Purge Valve	1/2"	- 1 No.
11.Brake Assembly		- 1 No.
12.1/2" SS Braded Hose with	- 2 Nos.	
both side ½" table	(one spare)	
(at least 3 mtr. run		

The Khoa Pan would be resting on 4 Nos. of MS Legs (ending in MS Flanges, Stationery Type/MS Frame with Flange-Tilting type) and the jacket would be designed to a working pressure of 6 kgs./sq.cm. All the MS parts would be painted with two coats of anti-corrosive epoxy primer followed with two coats of synthetic enamel paint of rose white color.

9. Vacuum Paneer Packing Machine

CAPACITY: UPTO 5 KG PACK SIZE - 02 CYCLES / MIN

- 1. The double chamber, double seal bar and trolley mounted type vacuum packaging machine shall be used for packing of paneer in the retail packing of 200 grams to 1000 grams or bulk packing of 4 kg in pre-formed pouches of multi-layer oxygen barrier film.
- 2. The trolley type model shall have AISI 304 lid with see through inspection window and the body fabricated out of stainless steel material confirming to AISI 304. All product contact parts shall be fabricated from food grade stainless steel material confirming to AISI 304. The size of the vacuum chambers shall be sufficient to hold at least five filled pouches of 1000 gms on two seal bars located one on each side of the machine or one pack of 4 kg at a time.
- 3. The machine shall have facility for inert gas flushing. It shall also have additional seal pressure arrangement. Approximate bag size may be taken as 8" W X 10" L for 1 kg product.
- 4. Chamber and lid shall be fabricated out of 10 gauge and housing shall be fabricated out of 16 gauge stainless steel material confirming to AISI 304. The lid shall have see through acrylic inspection window.
- 5. The chamber shall be suitable to hold minimum five packs of retail size at a time or one pack of bulk size.
- 6. **Seal Bar**: The vacuum machine shall be provided with two seal bar, one on each side. The silicon pressure pad and seal bar shall be suitable for sealing multi-layer oxygen barrier material of thickness up to 110 micro. The length of the seal bar is min 475 mm.
- 7. **Gas flushing**: The machine shall have in-built gas flushing facility to remove effectively air from the pouch and purge inert gas in the pouch as well as chamber. The flushing arrangement shall have necessary controls for calculated quantity of inert gas flushing per cycle.
- 8. **Seal pressure**: Machine shall be equipped with an in-built facility for applying additional seal pressure particularly when inert gas flushing is done or higher film thickness is used.
- 9. **Vacuum level**: The maximum vacuum level can be achieved on this machine shall be 99.9% (725 Hg) in any of the cycle and the vacuum level shall remain constant during the operation to achieve batter packing results. To achieve the desired vacuum level, latest design Toshniwal make oil free oil lubricated pump of capacity 35cu.m/hr with 1 HP three phase motor shall be provided.
- 10. **Additional features**: Digital microprocessor control with 10 memories and accuracy up to $1/100^{th}$ of a second for sealing operation.
- 11. **Capacity:** Suitable to seal retail packs of 200 gm to 1000 gm, 4 packs at a time or single bulk pack of 4 Kg. The cycle time for sealing shall be 2-cycles/ min. with full vacuum, loading and unloading time shall be at actual.

10. Sweet Curd / Plain Curd filling and sealing machine Capacity—1000 cups /hr (ROTARY)

FUNCTIONAL REQUIREMENT

The machine shall be used for automatic filling and sealing of sweet curd and plane curd in 80ml/100ml and 200ml/400ml. cups of different diameter/height. The product shall have minimum 20% milk total solid at a temperature of 40° Celcius.

Design consideration

- Filling/sealing capacity 1000 Cups/hour
- Flexibility in changing of dies within a limited time period.
- Volumetric filling in 80ml/100 ml and 200 ml/400 ml. of different diameter/height Cups.
- Should be suitable for High Impact Polystyrine cups and aluminium foil sealing.
- Double Track filling & sealing.
- PLC Based, servo system to facilitate change of speed and efficiency. Double sealing to ensure 0% leakage.
- Should be operated with 3 phase power supply 400V.

SCOPE OF THE BIDDER

- The bidder shall clearly mention the dimension of the machine, requirement of utilities like water, chilled water, steam compressed air, electrical load etc.
- Minor civil works like structural supports, S.S/MS pipe lines/fittings/ valves, electrical cables required for installation is within the scope of the bidder.
- The bidder shall draw all utilities/electrical lines from the main header at his own cost.
- Shifting of the machine to the work place for installation & commissioning.
- One years free after sale service from the date of handing over.

The machine should be supplied with the following spare items.

Dies

```
80 ml /100 ml -1 set 200 \text{ ml}/400 \text{ ml} -1 \text{ set} PLC Control spares -1 set Consumable items like rubber rings/gaskets -1 set Tools/Tackels -1 set
```

NOTE: Stage inspection shall be made by the OMFED officials prior to delivery.

The bidders are advised to visit site on any working day to assess actual requirement.

11. **Ghee Vat – 500ltr**

FUNCTIONAL REQUIREMENTS:

Ghee Boiler (steam heated kettle) shall be used for the manufacture of ghee from butter or cream.

DESIGN REQUIREMENTS:

CAPACITY- 500Litres.

Construction features:

Triple walled, having jacket on shell & bottom, top mounted, vertical agitator insulated

Finish

All welded joints to be ground smoothly. All stainless shell surfaces are to be polished to 150 grits or 2B mill finish.

SCOPE OF SUPPLY:-

Inner Shell:

The inner shell cylindrical body & hemispherical bottom shall be fabricated from stainless steel plate of thickness 6mm thick confirming to AISI316 respectively.

Intermediate Shell:

The intermediate shell cylindrical body & hemispherical bottom shall be fabricated from stainless steel plate of thickness 6mm thick confirming to AISI 304

Outer Shell:

The outer shell cylindrical body & bottom dish shall be fabricated from stainless steel plate of thickness 2mm & 3mm thick confirming to AISI 304 respectively.

Insulation:

The entire intermediate jacket shell & hemispherical bottom shall be insulated as follows.

1ST Layer:- 50MM thick resin bonded fiber glass having density of 24Kg/m3 shall be applied with chicken netting.

2nd Layer:- 50MM thick resin bonded fiber glass having density of 24Kg/m3 shall be applied with chicken netting.

ACCESSORIES:

Grider: Stainless steel 5 mm thick girder shall be provided for mounting of agitator & top cover. -01 No.

Covers:

Semicircular removable stainless steel (AISI 316) covers of 2mm thick with lifting handles.-1No

Agitator: Sweeping type stainless steel (AISI316) agitator with vertical geared motor of 1HP(Three phase) @20RPM complete with oil seal, supporting arrangement, support on shell & bottom etc. The agitator shaft shall be a solid rod -01No

Leg: Stainless steel legs & bracing pipe shall be provided with stainless steel ball feet. The ball feet shall have provision for the height adjustment of 50mm.

Steam Inlet: Steam inlet connection shall and outside in a flange and counter flange but without valves. The places mentioned below shall be stiffened with stainless steel padding. Where steam inlet pipe joints the intermediate shell. Where steam hits on the outer surface of inner shell.

Condensate Outlet:

Condensate outlet with strainer, float type steam trap and by pass arrangement shall be provided. It shall also be provided with suitable flanges joint for each removable component.

Pressure relief valve and pressure safety valve-These valves shall be provided in the system will save the Ghee boiler from accidents.

Dial Thermometer: Standard thermometers shall be fitted for temperature measurement.

Air Vent:

34" Socket end connection with Auto air vent valve at top most portion of the steam jacket-1No.

Thermo well:

Thermo well (made from stainless steel confirming to AISI316) and suitable connection shall be provided in the outer shell for fixing steam and dial thermometer to measure the temperature of product. The portion of the thermo well, which is in the steam jacket, shall be insulated with rock wool or equivalent and totally shrouded so that the insulation does not come in contact with stem & is within the scope of supply.

1No.

Bottom Outlet:

AISI 316 vertical outlet having stainless steel straight through plug type flanged valve ending in complete stainless steel union. The outlet shall be at a clear height of 650mm from the finished floor level to facilitate placement of can under it. Size of outlet valve is 63.5MM.

Side Outlet.

Horizontal stainless steel outlet with stainless steel angular flanged valve ending in complete stainless steel union for taking out clear ghee. Size of side outlet valve is 63.5mm.

TESTS.

The manufacturer at their works should conduct the following tests:

- i) Dye penetration test for weld joints.
- ii) Water fill-up test of inner vessel for water for water tightness.
- iii) Hydro test pressure of jacket at 5Kg/cm2. Pressure.

12. Air Compressor – 15 HP capacity

Tank mounted, Rotary screw type, Oil injected, air cooled, single stage, air cooled pack having actual free delivery of 56.4 CFM (96 m³/hr) @ 7.5 bar or 48.9 cfm (83.4 m³/hr) @10bar or 40.3 cfm (68.4 m³/hr) @13 bar. The compressor should be could be coupled with 11.0 KW (15HP) TEFC squirrel cage electric motor having IP 55 protection and class 'F' insulation. The compressor should be equipped with "ELEKTRONIKON 001 REGULATOR". The entire equipment should be housed inside a sound absorption canopy which limits the sound level to 67 db (A). the compressor is integrated with suitable refrigerant (R 134a) type Air Dryer within same canopy. The compressor is mounted on 270ltr horizontal receiver tank. Motor RPM - 2990.

Should be equipped with special filter UD 25+ range high effiency coalescing filter removing liquid water and oil Aerosol to 0.00009 mg/m^3 (0.00009 ppm) and particles down to 0.00009 micron.

13. CIP System – 1KLPH

FUNCTIONAL REQUIREMENTS

GENERAL DESCRIPTION

All milk handling equipment including heat exchanger, storage tank, pumps, road milk tankers, inter-connecting pipes and fittings would be cleaned by this system.

CAPACITY

It should be suitable for a product dairy handling 30,000 L/day. It should consist of the following.

- a. Alkali storage tank with steam heating system capacity, 1100 L. -1 no.
- b. Acid storage tank with steam heating arrangement capacity, 1100 L. -1 no.
- c. Hot water tank with steam heating system capacity, 1100 L. -1 no.
- d. Raw water tank capacity 1100 L 01 no

OPERATING PARAMETERS

Working pressure – 2 kg / cm²

Working temperature: a) acid & lye solution - 75°c

b) Hot water - 95°c

Chemicals to be handled: 1% solution of sodium hydroxide

1% solution of nitric acid

DESIGN REQUIREMENTS

The tank should be vertical and cylindrical in shape

The inner shell, bi-sectional top cover and flat bottom should be fabricated from 2 mm thick decaled stainless steel conforming to AISI 304.

The outer shell should be fabricated from 3 mm thick mild steel of commercial grade to cover protect and seal the thermal insulation completely and should be firmly fixed to the inner structure.

The tank should be designed to withstand bulging or any other defect under the operating condition mentioned above.

The bottom of the inner shell should be provided with generous slope towards the outlet for free and complete draining of liquid.

Thermal insulation of glass wool or equivalent suitable for an operating temperature of 100 degree Celsius should be provided on the cylindrical portion and bottom of the inner shell in two layers of thickness 50 mm each.

The outer MS shell should have a coating of anticorrosive epoxy primer followed by two coatings of chemical resistant paint of approved shade.

The outer surface must be smooth and free from buckles, dents, weld heads etc.

Each tank should include the following:

Two nos. 51 mm dia CIP return inlets of SS near the top of the tank with SS flanges and counter flanges.

One nos. 51 mm dia water inlet of SS near the top of the tank with SS flanges and counter flanges.

Two nos. 63 mm dia outlet of SS near the bottom of the tank with SS flanges and counter flanges.

One no.51 mm dia drain of SS with SS flanges, counter blank flange and neoprene or equivalent gasket.

One no.63 mm dia. Over flow pipe.

One no. Pocket for temperature sensing unit.

One no. SS capillary type dial thermometer of range 0 to 150 °c

Suitable steam distribution system (SS pipe coil for acid and alkali tanks and steams sparser for hot water tank).

Four nos. tubular Ms legs of 300 mm height with SS cladding should be provided with SS ball feet capable of 50 mm vertical adjustment.

One no. Thermostatic valve on the steam inlet line with sensing element going into the pocket mentioned above this valve is intended to maintain the temperature of the liquid inside tank at the desired level.

One no. Perforated SS basket for lye is to be provided.

The C.I.P system shall include 4 nos of tank, 02 nos pump and 08 nos pneumatic valves

TESTS:

Dye penetration tests for all welding joints.

Water fill up test for inner shell before insulation

FINISH:

The inner SS vessel to be polished to 150-grit polish. All SS welds are to be ground smooth.

The outer MS surface to be finished with 2 coats of epoxy coat over 2 coats of anticorrosive primer.

SECTION - VI COMMERCIAL BID

			Quant	Unit Rate (Rs.)		Total Amount (Rs.)			
SI No	Name of equipment	Capacity	· ·	Supply	Erection	Supply	Erection	Total	
1	Online Milk Pasteuriser	5KLPH	1						
2	Online Milk Homogeniser	5KLPH	1						
3	Online Cream Separator	5KLPH	1						
4	Milk Can Washer	600 Cans/hr.	1						
5	Milk Silo	10 KL	1						
6	Two Stage PHE	1KLPH	1						
7	Multi Purpose Vat	1 KL	1						
8	Khoa / Rabidi Pan	240 Ltr	1						
9	Vacuum Paneer Packing Machine	Standard	2						
10	Sweet Curd / Plain Curd filling and sealing machine	1000 cups /hr	1						
11	Ghee Vat	500ltr	1						
12	Air Compressor	15 HP	1						
13	CIP System	1KLPH	1						
	Sub - TOTAL								
	GST (%)								
	Total								

N:B: Price quoted should be on FOR destination basis, inclusive of GST, all other taxes, duties, royalties, packing & forwarding charges, transportation, insurance and other incidental charges, loading & unloading charges etc. as applicable. Bidders are required to give break up of unit rates & quantities of each & all items to be supplied for the purpose of the contract.

Section VII

FORM OF BID

Bidders are required to fill up all the blank spaces in this form of Bid:

Name and address of OMFED : ORISSA STATE CO-OP. MILK PRODUCERS'

FEDERATION LTD.,

D-2, SAHEED NAGAR, BHUBANESWAR-751007,

ORISSA

Description of works : SUPPLY, INSTALLATION, TESTING AND

COMMISSIONING, AND TRIAL RUN OF DAIRY EQUIPMENTS AT TIRTOL DAIRY OF OMFED.

Dear Sir,

that period.

1.0	Having examined the bidding documents including conditions of contract, Specifications, schedule of quantities and drawings included in or referred to in the bidding documents including Addenda Nos.			
	Receipt of which is hereby duly acknowledged, for the execution of above mentioned			
	works, we, the undersigned offer to supply and deliver goods and services including			
	installation & commissioning as detailed in the price schedule, and maintain whole of the			
	·			
	said works, in conformity with the said conditions of Contract, specifications and			
	schedule of quantities for the sum of Rs(Rupees			
	only) or such other sum as may be ascertained in accordance with			
	the schedule of prices attached herewith and made part of this bid and the said technical			
	specifications, drawings and conditions.			
2.0	We, undertake, if our bid is accepted to commence the works within 15 days of receipt of the notification of award, and to complete and deliver the whole of the above said works comprised in the contract within*days calculated from the day of the receipt of the Notification of Award.			
3.0	If our bid is accepted we will furnish a security in the form of bank guarantee (as per the format provided in this bidding document) to be jointly and severally bound us for the due performance of the Contract, in amount of 10% of the above named sum in accordance with the conditions of Contract.			
4.0	We agree to abide by this bid for the period of 90 days from the date of bid opening, and			
	it shall remain binding upon us and may be accepted at any time before the expiry of			

5.0	Unless and until an agreement is prepared and executed, this bid, together with your written acceptance thereof, shall constitute a bidding contract between us.					
6.0	We understand that you are not bound to accept the lowest or any bid you may receive.					
	Dated this day of20					
	Signature					
	In the capacity of					
	Duly authorized to sign the bid for and on behalf of					
	(In capital letters).					
	No. of days should be in confirmation to the period of completion given in clause 1.3 of section –I – Instructions to bidders.					

APPENDIX TO THE FORM OF BID

Condition of Contract	Clause No.		
Amount of Performance Security a) Bank draft b) Bank guarantee	06	10% of Contract value	
Minimum amount of third party insu	rance		
Period for commencement, from the Of receipt of letter of intent.	e date	30 days	
Time for completion from the date of receipt of letter of intent		2 months	
Rate of penalty for delay	24	0.5% of the contract Value /week or part thereof.	
Maximum limit of penalty	24	10%	
Period of maintenance (Defect liability period)	and ac	12 months from the date of completion of work, cceptance by Engineer-in-charge.	
Time within which the payment would be made after the certificates Receipt of Goods /completion of or		30 days	
Dated thisday of	20		
		Signature in the capacity Of, duly authorized to Sign the bid for and on behalf of	
		(In capital letter)	

SECTION VIII

QUALIFICATION APPLICATION

All the bidders who are interested in submitting this bids against this tender for the items must submit the qualification application along with the information in the following formats together with the relevant documentation.

SCHEDULE -I

FINANCIAL BISINESS AND TECHNICAL CAPABILITY

	Name and address of the bidder :	
	Telephone No :	
1.	on (Attach a copy).	
2.	Latest profit and loss statement fromtofiled with on (Attach a copy).	
3.	Financial position (in the respective currency)	
A)	Cash	
b)	Current assets	
c)	Current liabilities	
D)	Working capital	
e)	Net worth	
4.	Total liabilities:	
a)	Current ratio: Current assets to current liabilities.	
b)	Acid ratio test: cash temporary investment held in lieu of cash and current receivable current liabilities.	to
c)	Total liability to net worth.	
5.	Net sales (in the respective currency)	
a)	Current period	
b)	During the last financial year	
c)	During the year before last financial year	

6.	Net pro	ofit bef	fore tax				
a)	Curren	t period	d				
b)	During	the las	t financial year				
c)	During	the yea	ar before last fi	nancial year			
	The pro	ofit and	loss statemen	ts have been	certified through	r	
			By		.		
7. Bido	ders Fir	nancial	arrangement	s (check app	ropriate item)		
a) Owr	n resour	ces					
b) Ban	k credit	S					
c) Othe	er speci	fy					
8. Cert	tificate c	of financ	cial soundness	from bankers	of bidders		
9. Sale	es						
Catego	ory	Value	of current orde	rs to	value of antic	pated sales	
		Be exe	ecuted in respe	ctive	for next finance	cial year in	
			Currency		respective cu	rrency	
A)			nent				
B)	Comm	ercial					
10. Lic	ensed o	apacity	/ to manufactur	e:			
Descri	ption	Size	Licensed	No. of units	Manufactured	Second	
of equi	ip.	Сар.	Capacity	current year	last year	last year	

11. List, if any, of bidders rate contract with the following organizations.

	Organization	Yes/No	If yes, date contract finalized
a.	Directorate General of		
	Supplies & Disposal,		
	Government of India.		
b.	Central Equipment Stores Purchase organization for		
	State Governments.		

- 12. Describe quality control Organization, if any and give the organization chart.
 - a) Are goods offered subject to batch test random sampling or full 100% test for quality?
 - b) Are tests carried out by factory employees or by a separate testing agency?
 - c) Are independent quality control organization checks made and certificates issued?

13. Income tax clearance

Following documents with regard to income tax clearance should be submitted along with application.

- a) Details of Income tax registration
- b) Last Income tax clearance certificate.

SECTION -IX

Form of Agreement On Non-Judicial Stamp paper of Rs.100/-

THIS		GREEMENT 20	is	made	and	executed	on	the	day	of
body office	corpora at Sal ssion s	ate under the cheed Nagar, shall, unless re	ORISS. Bhubar epugna	A CO-OPE neswar - 7 ant to the o	RATIVE '51007 (SOCIETIES A herein after re or meaning the of the	ACT and eferred	l having to as C clude th	its regis MFED v	tered which
conte admir	xt or nistrator	meaning the	reof, i actor) c	nclude the	e heirs, ER PAR	expression sh successors, T. ks should be e	assign	ees, ex	•	
suppl perfo	y of s	such goods	and s	ervices, ir	ncluding	, accepted a installation, OW THIS AG	testing,	commi	ssioning	and
1.0		-		=		s shall have ns of Contract			_	s are
2.0	The f	following docu			leemed	to form and b	e read	as cons	strued as	s part
	i) ii) iii) iv) v) vi) vii) viii)	This Form of This Letter of The Said bid The Technic The Schedu The Drawing The Schedu Special Cor	of Acce d, Appe cal Spe ule of Q gs ule of S	ptance endix and the edifications enantities upplement	ary Infor	Schedule Ther	reof			

- ix) General Conditions of Contract
- x) Schedule of Materials to be issued by OMFED
- xi) Form of Bank Guarantees
- 3.0 The aforesaid documents shall be taken as complementary and mutually explanatory of one, another, but in the case of ambiguities and discrepancies shall take precedence in the order set out above.
- 3.0 In the consideration of the payment to be made by the OMFED to the Contractor as herein after mentioned, the Contractor hereby covenants with the OMFED to execute, complete and maintain the works in conformity in all respects with the provisions of the Contract.
 - * The bidder shall not fill up this form.
- 4.0 The OMFED shall hereby covenants to pay the Contractor in consideration of the execution, completion and guaranteeing of the works the contract price at the times and in the manner prescribed by the Contract.

IN WITNESS WHEREOF the parties hereto have caused their respective Common seals to be hereunto affix the day, month and year first above written.

Signed, sealed and delivered for

And on behalf of the within

named OMFED by the hands of its

Authorised signatory.

Authorised Signatory

ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD.

WITNESS:	
1) Signature	
Name and address	
2) Signature	
Name and address	
Signed, sealed and delivered for	
And on behalf of the within	
Named Contractor, the other part.	
	Authorised Signatory

In the presence of:

CONTRACTOR

In the presence of:

WITNESS:

1) Signature

Name and address

2) Signature

Name and address

SECTION-X ACCEPTABLE FORM OF BANK GUARANTEE

Proforma of Bank Guarantee for Bid Security On Non-Judicial Stamp Paper of Rs.100/-

Bank Guarantee no.	Date:
This deed of guarantee made this	s of the Bank), hereinafter referred to kt or the meaning thereof includes its RISSA STATE CO-OPERATIVE MILK to as the OMFED) which expression
Whereas the OMFED has invited bids for the supply, instrun and guaranteeing of the proposed	
AND WHEREAS M/S (Name and the submitted their bids (hereinafter referred to as the Tender OMFED an amount indicated in the tender notice as per the documents. AND WHEREAS the OMFED is also willing the payment by demand draft of any amount equivalent to the deposited by the bidder to the OMFED which guarantee the day of the opening of the bids.	address of the bidders) who having er) and have agreed to deposit to the ne terms and conditions of the bidding to accept a Bank guarantee in lieu of amount of bid security required to be

In consideration of the OMFED having agreed to consider the bid proposals having submitted by the bidder without depositing the amount of bid security and against this Bank guarantee, we (name and the address of the Bank) hereby undertake and guarantee to make payment to the OMFED the amount of bid security or any part thereof not deposited by the bidder to the OMFED at any time (time being the essence of the Contract) when the OMFED asks for the

same as per the terms and conditions of the bidding documents within 120 days from the date of opening of the bids.

In case the OMFED puts forth a demand in writing on the Bank for the payment of the amount in full or in part against this Bank Guarantee, the Bank will consider that such demand by itself is a conclusive evidence and proof that the bidder has failed in complying with the terms and conditions stipulated by the OMFED in its bidding document and payment will be made to the OMFED without raising any disputes regarding the reasons for such failures on the part of the bidder.

The Bank shall not be discharged or released from this guarantee by any arrangement between the bidder and the OMFED with or without the consent of the Bank or any alternations in the obligations of the parties or by an indulgence, forbearance shown by the OMFED to the bidder.

This guarantee shall be in addition to and without prejudice to any other securities or remedies which the OMFED may have or hereafter possess against the bidder and the OMFED shall be under no obligations to marshal in favour of the Bank any such securities or fund or assets that the OMFED at its absolute discretion may vary, exchange, renew, modify or refuse to complete or enforce or assign any security or instrument.

The Bank agrees that the amount hereby guaranteed shall be due and payable to the OMFED on OMFED's serving with a notice requiring the payment of the amount and such notice shall be served on the Bank either by actual delivery thereof to the Bank or by dispatching thereof by to the Bank by registered post at the address of the said Bank. Any notice sent to the Bank at its address by registered post shall be deemed to have been duly served on the Bank notwithstanding that the notice may not in fact have been delivered to the Bank.

In order to give full effect to the provisions of this guarantee the Bank thereby waives all rights inconsistent with the above provisions and which the Bank might otherwise as a guarantor be entitled to claim and enforce.

The guarantee shall remain in force untilor a claim is preferred against the bank within three mont OMFED under this guarantee shall cease and the bank sall liabilities hereunder.	ths from the said date all rights of the
Notwithstanding anything contained here before, our liability Rs	only) being the amount of
Place	Signature
	Seal
	Code no.

Note: Bidders should ensure that the seal and code no. of signatory is put by the Bankers, before submission of the Bank guarantees.

Proforma of bank guarantee for Performance security On Non-judicial Stamp Paper of Rs.60/-

Bank Guarantee No.	Date:
This deed of guarantee made this	d address of the bank) hereinafter referred to e context or the meaning thereof includes its d the ORISSA STATE CO-OPERATIVE MILK referred as to the OMFED) which expression
Whereas the ORISSA STATE MILK CO-OPERA awarded a contract bearing No. M/s	on (Name and the address ctor, for the supply installation, commissioning,
And whereas the Contractor has agreed to submiguarantee to the OMFED as per the terms and contract which will be kept valid upto	conditions of the bidding documents. And thecalendar months from the date of bank d of maintenance) and whereas the bank and
OMFED, its legal representatives, successors, a the Contractor) their legal representatives, assign within the bidding document and the contract ord the time (time being the essence of the contract obligations there under and we further undertaken	ntee, undertake, promise and agree with the nd assigns that the within named(the name of nees will faithfully perform and fulfill everything er on their part to be performed or fulfilled, at act) and in manner therein provided, do all e and guarantee to make the payment to theonly). Being 10% of the contract value

everything within the bidding document and the contract order on their part to be performed or fulfilled, at the time and in manner therein provided and do not willfully and promptly do all obligations there under. In case the Contractor fails to perform or fulfill the contract as per the terms and conditions agreed upon, the OMFED is entitled to demand an amount equivalent to 10% of the contract value from the Contractor and the demand made by the OMFED itself will be conclusive evidence and proof that the Contractor has failed to perform or fulfill his obligations under the contract and neither the Contractor nor the bank shall be entitled to raise any dispute regarding the reasons for the failure of performance or fulfillment on any ground whatsoever.

We, (the name of the bank), do hereby undertake to pay an amount equivalent to 10% of the contract value, being the amount due and payable under this guarantee. Without any demur, merely on a demand from OMFED stating that the amount claimed is due by way of Non-performance of the contractual obligations as aforesaid by the contractor or by the reason of the contractor's failure to perform the said contractual commitments, any such demand made on the banks shall be conclusive as regards the amount due and payable by the bank under this guarantee. However, our liability under this guarantee shall be restricted to an amount not exceeding Rs._____ (Rupees_____ only being the amount equal to10% of the contract value.

We, the bank further agree that the performance security herein contained shall remain in full force and effect for a period of _____ calendar months from the date of the bank guarantee. (the period shall be till the end of period of maintenance) whichever is later or till the OMFED certifies that the terms and conditions of the said contract have been fully and properly carried out by the said Contractor and accordingly discharge the guarantee , unless a demand or a claim under this guarantee is made on us in writing by the OMFED on or before _____ (the date shall be 90 days after the end of the period of maintenance) we shall be discharged from all liabilities under this performance security hereafter.

We, the bank, further agree with the OMFED that the OMFED shall have the fullest liberty without our consent and without affecting in any manner our obligations hereunder to vary any of the terms and conditions of bidding document and the contract or to extend the time of performance by the said Contractor from time to time and any of the power exercisable by the OMFED against the Contractor and forbear or enforce any of the terms and conditions relating to the said bidding document and the contract and we shall not be relieved from or liability by reason of any such variation ,or extension being granted to the said contractor or for any forbearance, act or omission on the part of the OMFED to the said Contractor by any such matter or thing whatsoever which under the law relating to the sureties would but for this provision have effect of so relieving us. This guarantee shall be in addition to and without

prejudice to any other securities or remedies which the OMFED may have or hereafter possess in respect of the works executed or intended to be executed and the OMFED shall be under no obligation to marshal in favour of the bank any such securities or funds or asset that the OMFED may be entitled to receive or have a claim upon and the OMFED at its absolute discretion may vary, exchange, renew, modify or refuse to complete or enforce or assign any security or instrument.

The bank agrees that the amount hereby guaranteed shall be due and payable to the OMFED on serving us with a notice, requiring the payment of the amount and such notice shall be deemed to have been served on the bank either by actual delivery thereof to the bank or by dispatch thereof to the bank by registered post at the address of the bank.

been duly served on the bank notwith	, ,	ed post shall be deemed to have may not infact has been delivered
to the bank.		
In order to give full effects to the province inconsistent with the above Rs remain in force until preferred against the bank within three of the OMFED under the guarantees from all liabilities hereunder.	(Rupees and unless the guar ee months from the said c	Only). The guarantee shall rantee is renewed or a claim is date (the date of expiry) all rights
Place	Sign	nature
Date	S	eal
	Coc	de no.

Note:

The Contractor should ensure that seal and the code no. of the signatory is put by the bankers, before submission of the bank guarantees.

Proforma of Bank guarantee for advance payments On Non judicial stamp paper of Rs 40/-

In consideration of the ORISSA STATE CO-OP. MILK PRODUCERS' FEDN. LTD. (hereinafter called "the OMFED") having regard to grant advance of Rs						
(Rupees) to	M/s				
Having their office	at					_
	"the said contractor d	,	terms and co etween th		•	Order M/S.
for supply, installat	ion, commissioning,	trial-running	and guarante	eeing of		
(Hereinafter called	the " the order") on	production of	bank guarar	ntee for Rs		-
	only), W exceeding only) against ar	Rs		(Rupees	S	
reason of any brea	ich by the said contr	•	•		•	-
without any demur by way of loss or reasons of any bre order or by reason on the bank shall I guarantee and	hereby undertake in merely on a demand damage caused to each by the said consoler sof the contractor's perconclusive as registrall be(Rupees _	d from the Ol o or would be tractor of any failure to per pards the amo restricted	MFED stating e caused to of the terms form the said ount due and to an	that the amore or suffered be and condition order. Any su payable by the amount	unt claimed y the OMFI s contained uch demand	is due ED by in the made er this
said order and that or by virtue of the OMFED certifies the carried by the said a claim under this	(the bank), and effect during the tit shall be continued said order have been at the terms and contractor and acceptantee is made at liabilities under this	ne period thate to be enforced en fully paid conditions of cordingly dischangly us in writing	at would be ta ceable till all tand it's clain the said orden narge the guang on or befo	the dues of the ns satisfied or the have been arantee and ur	erformance e OMFED, or discharged fully and pro nless a dema	of the under, I or till operly and or

the fullest liberty without our consent and the fullest liberty without our consent and performance by the said Contractor from any of the terms and conditions refrom our liability by reason of any such comission on the part of the OMFED or and	r agree with the OMFED that the OMFED shall have and without affecting in any manner our obligation and conditions of the said order, to extend the time of time to time or to postpone for any time or from time to OMFED against the said Contractor and to forbear or relating to the said order and we shall not be relieved variation, or extension or for any forbearance, act of by indulgence by the OMFED to the said Contractor or ich under the law relating to the sureties would but for said.
We, (the bank), lascurrency except with the previous consent	stly undertake not to revoke this guarantee during its tof the OMFED in writing.
Rs (Rupees remain in force till the preferred against the bank within three mo	oove the liability of the bank Guarantee is restricted to Only). The guarantee shall and unless the guarantee is renewed or a claim is onths from the said date all rights of the OMFED under k shall cease and the bank shall be released and
Place	Signature
Date	Seal
	Code no.

<u>Note</u>

Note: Contractor should ensure that seal and code no. of the signatory is put by the bankers, before the submission of the bank guarantees.

SECTION --XI (1)

MANUFACTURER'S AUTHORIZATION FORM

No	Dated	
То		
Orissa State Co-op. Milk Prod	ducers Federation. Ltd.	
D-2, Saheed Nagar		
Bhubaneswar-751001		
ORISSA, INDIA		
Dear Sir,		
Sub: Tender Ref. No.		
We		_an established and reputable
		having factories at
and		do hereby authorize M/s (Name and address of
agents) to bid, negotiate and	d conclude the contract with yo	bu against Tender notice Ref. No.
for	the above goods manufactured l	by us.
No company or firm or individ	ual other than M/s	,
	are authorized	I to bid, negotiate and conclude the
J	5	

We hereby extend our full guarantee and warranty as per the General conditions of contract for

the goods offered for supply against this Tender notice by the above firm.

Yours faithfully,

(NAME)

For and on behalf of M/s.

(Name of Manufacturers)

Note: This letter of authority should bee on the letterhead of the manufacturing concern and should be signed by a person competent and having the power of attorney to bind the manufacturer.

SECTION-XI (2) MANUFACTURER'S AUTHORIZATION FORM

(Please see Clause 14.3 of instructions to bidders)

No	Dated	_
То		
Orissa State Co-op. Milk Pro	ducers' Federation. Ltd.	
D-2, Saheed Nagar		
Bhubaneswar-751007		
ORISSA		
Dear Sir,		
Sub: Tender Ref.No.		_
We		an established
	urers of and	
address of agents) to bid	l, negotiate and conclude the contra for the above goods manufactu	ct with you against bid
No company or firm or individ	dual other than M/s	
are authorized to bid, negotia specific IFB.	ate and conclude the contract in regard to	this business against this
•	arantee and warranty as per Clause 81 o d for supply against this invitation for bid b	-

Yours faithfully,

(NAME)

For and on behalf of M/s

(Name of manufacturers)

Note: This letter of authority should be on the letterhead of the manufacturing concern and should be signed by a person competent and having the power of attorney to bind the manufacturer.

SECTION - XII

TECHNICAL DEVIATION STATEMENT FORM

The following are the particulars of deviations from the requirements of the tender specifications.

CLAUSE		DEVIATION	REMARKS	
			(Including justificatio	n)
Dated-			Signature and seal of the Manufacturer / Bidder	
			Manufacturer / Bidder	
Note:				
	(1)		is no deviation, the stater nendorsement indicating "No	ment should be returned duly
	(2)	The technica prevail over the	al specifications furnished in	n the bidding document sha orming a part of our bid, excep

SECTION - XIII

POINTS BIDDERS SHOULD BEAR IN MIND

- I. BIDS CONTAINING DEVIATIONS FROM BIDDING DOCUMENT TERMS AND OTHER CONDITIONS MAY BE REJECTED.
- II. BIDS NOT ACCOMPANIED BY BID SECURITY (EARNEST MONEY DEPOSIT) SHALL BE SUMMARILY REJECTED.
- III. NON-COMPLIANCE WITH EVEN A MINOR TECHNICAL REQUIREMENT SHOULD BE SPECIFICALLY STATED BY THE BIDDERS.
- IV. BIDDERS SHOULD FURNISH THEIR COMPLETE ADDRESS FOR THE PURPOSE OF FURTHER CORRESPONDENCE PERTAINING TO BIDDING DOCUMENT.
- V. CORRECTIONS IN THE BID SHOULD BE NOTED OVER AND INITIALED AT THE PLACE OF CORRECTIONS.
- VI. NEGLIGENCE OF THE BIDDER IN PREPARING THE BID CONFERS NO RIGHT TO WITHDRAW THE BID AFTER IT WAS OPENED.
- VII. SPECIFICATIONS, CONDITIONS, SCHEDULES AND DRAWINGS OF BIDDING DOCUMENT CONSTITUTE AN INTEGRAL PART OF THE BID.
- VIII. ALL THE BIDS ALONGWITH ENCLOSURES, DRAWINGS AND TECHNICAL LITERATURE SHOULD BE IN ENGLISH ONLY.
- IX. BIDDING DOCUMENT SHALL BE GOVERNED AND INTERPRETED ACCORDING TO THE SYSTEM AND COMPONENTS UNDER TROPICAL CONDITIONS.
- X. ALL THE BIDDERS SHOULD SUBMIT QUALIFICATION APPLICATION IN THE GIVEN FORMATS WITH REQUIRED DOCUMENTATION.
- XI. BIDS SHOULD BE KEPT VALID FOR ACCEPTANCE FOR A PERIOD OF ONE YEAR FROM THE DAY BIDS ARE OPENED.
- XII. THE BIDDING DOCUMENT SHALL BE GOVERNED AND INTERPRETED ACCORDING TO THE LAWS OF THE UNION OF INDIA.
- XIII. ALL BIDDERS ARE URGED TO SUBMIT PROMPTLY WRITTEN REQUESTS ON MATTERS WHERE CLARIFICATIONS OR ADDITIONAL INFORMATION ARE DESIRED, NOT LATER THAN SEVEN DAYS BEFORE BIDS ARE DUE TO OPENING. NO EXTENSION IN DUE DATE OF SUBMISSION OF BIDS WILL BE ALLOWED ON THIS GROUND.
- XIV. ALL THE BIDDERS SHOULD QUOTE FOR THE ITEMS AS PER THE SPECIFICATIONS AND DETAILS GIVEN IN THIS BIDDING DOCUMENT ONLY. IN CASE, ALTERNATIVE DESIGNS ETC. ARE TO BE OFFERED BY THE BIDDERS, THEY MAY DO SO BUT THIS SHOULD BE STATED SEPARATELY IN THE OFFER.ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LIMITED RESERVES ITS RIGHT TO ACCEPT OR REJECT SUCH ALTERNATIVE OFFERS, WITHOUT ASSIGNING ANY REASONS THEREOF TO THE BIDDERS.
- XV. THE BIDDERS WHO QUOTE FOR SUPERVISION AND COMMISSIONING OF ANY EQUIPMENT SHOULD ALSO INDICATE THE PRICES IN THE BID SEPARATELY. THE SUPERVISION OF COMMISSIONING WOULD INCLUDE CHECKING THE INSTALLATION AND COMMISSIONING THE PLANT TO GIVE THE RATED OUTPUT.
- XVI. MANAGING DIRECTOR, ORISSA STATE CO-OPERATIVE MILK PRODUCERS' FEDERATION LTD. RESERVES THE RIGHT TO ACCEPT OR REJECT ANY OR ALL BIDS WITHOUT ANY EXPLNATION TO BIDDERS.
